

Remote Sensor Condensate Pump

MODEL: **PART No:**
HAR-3 **861017**
HAR-5 **861018**

**1 YEAR
WARRANTY**



A range of remote sensor condensate pumps for use in all types of AC applications where the sensor can either be mounted directly into the indoor unit.

Suitable for all type of AC equipment up to 15KW (45,000 BTU) and pumping heads up to 26ft.

The pumps come standard with high level alarm volt-free contacts and motor overload protection.

KEY FEATURES

- Quiet and no vibration
- Highly reliable
- High flow rate
- Compact construction and easy assembly
- Compact modern design

TECHNICAL SPECIFICATION

Model	HAR-3	HAR-5
Input Voltage	100-230V, AC 50Hz-60Hz	100-230V, AC 50Hz-60Hz
Pumping Head	26ft	26ft
Max Flow Rate	3.17 Gal/hr	5.28 Gal/hr
Tank Capacity	1.18 Fluid Ounces	1.18 Fluid Ounces
Noise Level	19dBA	21dBA
Maximum Cooling Capacity	8kW (30,000BTU)	15kW (45,000BTU)
Ambient Temperature	0 - 122° F	0 - 122° F
Power Consumption	3W	3W

FLOW RATES

HORIZONTAL RUN	PERFORMANCE				
	0ft	6ft	13ft	19ft	26ft
HAR-3					
6ft	3.17 Gal/hr	2.64 Gal/hr	1.84 Gal/hr	1.58 Gal/hr	1.32 Gal/hr
16ft	2.64 Gal/hr	2.37 Gal/hr	1.58 Gal/hr	1.05 Gal/hr	0.79 Gal/hr
32ft	2.37 Gal/hr	2.11 Gal/hr	1.32 Gal/hr	-	-
49ft	2.11 Gal/hr	1.84 Gal/hr	-	-	-
HAR-5					
6ft	5.28 Gal/hr	4.75 Gal/hr	2.64 Gal/hr	2.37 Gal/hr	2.11 Gal/hr
16ft	4.49 Gal/hr	3.96 Gal/hr	3.43 Gal/hr	2.90 Gal/hr	2.11 Gal/hr
32ft	4.22 Gal/hr	3.17 Gal/hr	2.64 Gal/hr	2.11 Gal/hr	1.58 Gal/hr
49ft	3.69 Gal/hr	3.17 Gal/hr	2.11 Gal/hr	1.32 Gal/hr	-

DIMENSIONS

