

# Remote Sensor Condensate Pump

**MODEL:**      **PART No:**  
**HAR-3**        **861017**  
**HAR-5**        **861018**

**1 YEAR  
WARRANTY**



A range of remote sensor condensate pumps for use in all types of AC applications where the sensor can either be mounted directly into the indoor unit.

Suitable for all type of AC equipment up to 15KW (45,000 BTU) and pumping heads up to 26ft.

The pumps come standard with high level alarm volt-free contacts and motor overload protection.

## KEY FEATURES

- Quiet and no vibration
- Highly reliable
- High flow rate
- Compact construction and easy assembly
- Compact modern design

## TECHNICAL SPECIFICATION

| Model                    | HAR-3                  | HAR-5                  |
|--------------------------|------------------------|------------------------|
| Input Voltage            | 100-230V, AC 50Hz-60Hz | 100-230V, AC 50Hz-60Hz |
| Pumping Head             | 26ft                   | 26ft                   |
| Max Flow Rate            | 3.17 Gal/hr            | 5.28 Gal/hr            |
| Tank Capacity            | 1.18 Fluid Ounces      | 1.18 Fluid Ounces      |
| Noise Level              | 19dBA                  | 21dBA                  |
| Maximum Cooling Capacity | 8kW (30,000BTU)        | 15kW (45,000BTU)       |
| Ambient Temperature      | 0 - 122° F             | 0 - 122° F             |
| Power Consumption        | 3W                     | 3W                     |

### FLOW RATES

| HORIZONTAL RUN | PERFORMANCE |             |             |             |             |
|----------------|-------------|-------------|-------------|-------------|-------------|
|                | 0ft         | 6ft         | 13ft        | 19ft        | 26ft        |
| <b>HAR-3</b>   |             |             |             |             |             |
| 6ft            | 3.17 Gal/hr | 2.64 Gal/hr | 1.84 Gal/hr | 1.58 Gal/hr | 1.32 Gal/hr |
| 16ft           | 2.64 Gal/hr | 2.37 Gal/hr | 1.58 Gal/hr | 1.05 Gal/hr | 0.79 Gal/hr |
| 32ft           | 2.37 Gal/hr | 2.11 Gal/hr | 1.32 Gal/hr | -           | -           |
| 49ft           | 2.11 Gal/hr | 1.84 Gal/hr | -           | -           | -           |
| <b>HAR-5</b>   |             |             |             |             |             |
| 6ft            | 5.28 Gal/hr | 4.75 Gal/hr | 2.64 Gal/hr | 2.37 Gal/hr | 2.11 Gal/hr |
| 16ft           | 4.49 Gal/hr | 3.96 Gal/hr | 3.43 Gal/hr | 2.90 Gal/hr | 2.11 Gal/hr |
| 32ft           | 4.22 Gal/hr | 3.17 Gal/hr | 2.64 Gal/hr | 2.11 Gal/hr | 1.58 Gal/hr |
| 49ft           | 3.69 Gal/hr | 3.17 Gal/hr | 2.11 Gal/hr | 1.32 Gal/hr | -           |

### DIMENSIONS

