

LTP-1

- 2 Gallon Polypropylene Reservoir
- Unitized construction
- Suds-proof design
- Fits inside 24" base cabinets and vanities
- Fits under utility sinks
- Allows sink installation without breaking concrete to drain
- No main stack vent connection required (N.S.P.C. Section 11.7.9 Check Local Codes)
- Simple installation saves time

Note: Actual flow will vary with line losses.

SPECIFICATIONS

Model	LTP-1
Current	5.0 A
Voltage	115 V
Motor Power	1/4 hp
Motor Speed	1725 rpm
Discharge OD	1" FNPT
Inlet Size	1 1/2 inches
Inlet Connection Type	FNPT
Head Size	13 ft
Weight	24 lb
Flow Rate at Lift of 4'	44.0 gpm
Flow Rate at Lift of 8'	34.5 gpm
Flow Rate at Lift of 6'	2370 gal/h

Flow Rate at Lift of 12'	432 gal/h 7.5 gpm
Flow Rate at Lift of 16'	4.7 gpm
Cord and Plug	8 ft
Auxiliary Switch	No
20' Tubing	No
Shut off	13 ft
Reservoir	2 gal
Unit Dimensions (W x D x H)	10" x 12" x 17"
Width	10 inches
Depth	12 inches
Height	17 inches
Max. Temperature	130 °F
Mast. Ctn.	1 pc