## PRODUCT INFORMATION PACKET



Model No: 5KCR49WN0270T Catalog No: CG381 2,1725,DP,56HZ,1/60/115/208-230 Open Drip Proof (ODP)



Regal and Marathon are trademarks of Regal Beloit Corporation or one of its affiliated companies.

©2018 Regal Beloit Corporation, All Rights Reserved. MC017097E





## **Nameplate Specifications**

Output HP	2 Hp	Output KW	1.5 kW
Frequency	60 Hz	Voltage	115/208-230 V
Current	22.0,10.9-11.0 A	Speed	1725 rpm
Service Factor	1.15	Phase	1
Efficiency	72 %	Duty	Continous
Insulation Class	В	KVA Code	L
Frame	56HZ	Enclosure	Drip Proof
Overload Protector	AUTO	Ambient Temperature	40 °C
Drive End Bearing Size	6205	Opp Drive End Bearing Size	6203
UL	Recognized	CSA	Yes
CE	N		

## **Technical Specifications**

Electrical Type	Capacitor Start Capacitor Run(CSCR)	Starting Method	SM
Poles	4	Rotation	Selective Counterclockwise
Mounting	Rigid base	Motor Orientation	Any
Drive End Bearing	BALL	Opp Drive End Bearing	BALL
Frame Material	Rolled Steel	Overall Length	14.33 in
Frame Length	9.63 in	Shaft Diameter	0.880 in
Shaft Extension	2.25 in		
Outline Drawing	52A111881P1	Connection Diagram	52A105383AC

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created: 06/29/2018



