



Customer information packet

ECP2276T-5

7.5HP, 1180RPM, 3PH, 60HZ, 254T, 0954M, TEFC, F

Class - CLI GP A,B,C,D

Division - Division II

Specifications

Enclosure	TEFC
Frame	254T
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	CL I GP A,B,C,D
Haz Area Division	Division II
Motor Letter Type	Three Phase
Output @ Frequency	7.500 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	575.0 V @ 60 HZ
Agency Approvals	CSA EEV NEMA PREMIUM NEMA_PREMIUM UR CCSA US
Ambient Temperature	40 °C
Auxillary Box	No Auxillary Box
Auxillary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	1.0
Current @ Voltage	8.700 A @ 575.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	91.7 %
Electrically Isolated Bearing	Not Electrically Isolated
Enclosure Modification	Severe Duty Features
Feedback Device	NO FEEDBACK
Front Face Code	Standard

Part detail

Revision	AX
Type	AC
Mech. spec.	09J371
Base	
Status	PRD/A
Elec. spec.	09WGY264
Layout	09LYJ371
Eff. date	09-12-2024
CD Diagram	CD0006
Poles	06
Leads	3#12
Proprietary	False
Created date	08-29-2010

Front Shaft Indicator	None
Haz Area Temp Code	T3C
Heater Indicator	No Heater
High Voltage Full Load Amps	8.7 a
Insulation Class	F
Inverter Code	Inverter Ready
KVA Code	J
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	1800 rpm
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	3 @ 12 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	0954M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	24.78 IN
Power Factor	71
Product Family	Super-E Chemical Processing
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.625 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	1180 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None

Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3995ABBL																						
CAT #		ECP2276T-5					SER					CC		010A								
SPEC		09J371Y264					RATING		40C AMB-CONT													
HZ		VOLTS			AMPS			RPM		HP		CODE		SF		DES		PF		NEMA NOM. EFF		
60		575			8.7			1180		7.5		J		1.15		A		71		% 91.7 %		
																		% %				
PH		3	CL		F	MAX RPM		1800	MAX CORR KVAR			4	USABLE AT 208V				N/A					
IP55		FR		254T		ENCL		TEFC		DE BRG		6309		ODE BRG			6309					
GREASE		POLYREX EM									MTR WT			333		LBS						
USABLE AT		N/A																				
CL I DIV 2 GRPS A,B,C,D										CL I ZONE 2 GRPS					IIA,IIB,IIC			TEMP T		160	C	
1.0 SF ON PWM INVERTER					POWER					INV TEMP CL					180	C						
CHP		60-90		HZ		1.5:1	CT		1.0-60		HZ		60:1		VT		0-60		HZ		1000:1	
SPACE HEATER LEADS H1-H2:										TIE LIKE NUMBERS					TOGETHER							
V				A				W				MAX SPACE HEATER TEMP										

Accessories

Part number	Description	Multiplier
09-1309	C FACE KIT	A8

AC Induction Motor Performance Data

Record # 1931

Typical performance - not guaranteed values

Winding: 09WGY264-R001			Type: 0954M		Enclosure: TEFC			
Nameplate Data			575 V, 60 Hz: Single Voltage Motor					
Rated Output (HP)		7.5	Full Load Torque		33.3 LB-FT			
Volts		575	Start Configuration		direct on line			
Full Load Amps		8.7	Breakdown Torque		102 LB-FT			
R.P.M.		1180	Pull-up Torque		41 LB-FT			
Hz	60	Phase	3	Locked-rotor Torque		60 LB-FT		
NEMA Design Code		A	KVA Code	J	Starting Current		58 A	
Service Factor (S.F.)		1.15	No-load Current		4.6 A			
NEMA Nom. Eff.		91.7	Power Factor		71	Line-line Res. @ 25°C		1.37 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		32°C		
S.F. Amps				Temp. Rise @ S.F. Load		42°C		
				Locked-rotor Power Factor		26		
				Rotor inertia		4.34 lb-ft²		

Load Characteristics 575 V, 60 Hz, 7.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	33	53	61	71	78	80	75
Efficiency	84.9	90.6	91.8	91.9	91.4	90.5	91.6
Speed	1196	1192	1188	1183	1178	1173	1180
Line amperes	5.1	5.9	7.5	8.7	9.8	11.5	9.36


ABB Motors and Mechanical Inc.


WINDING # 09WGY264

Typical performance - not guaranteed values.



7.5 HP 3 PH 60 HZ 1180 RPM 575 V 0954M

TORQUES (LB-FT): PO=102 PU=41 LR=60 LRA=58





CD0006



NOTES:

1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.
2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

CD0006

REV. DESC: ADD CLASS CONN00000007

REV. LTR: E

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\141

REVISED: 10: 24: 49 02/19/2019

BY: ENBRIRO

MTL: -



BALDOR - RELIANCE®

3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED

SH 1 of 1