



CR15-H


Parts List & Kits

Contents

Parts List
Spare Part Kits
Accessories
Special Tools
Standard Tools
Tools for Torques



Exploded View CR15-H



TM047924

Parts List & Kits CR15-H

Pos. No.	Part Description	Model	Stages	No. Used	Comments/Dimensions	B.O.M. Ref. No.	Material No.	Included in kits ?
PARTS LIST								
1	Adapter for Motor Stool		4-6	1	For NEMA, 213/215TC, 7.5 - 10HP	96476208		No
2	Motor Stool		7-10	1	For NEMA, F254TC, 15-20HP	96486329		No
			2/1	1	NEMA, 56C, .75 - 2.0HP	96486287		No
			2-3	1	NEMA, 182TC, 3 - 5HP, (High)	96486311		No
			4-6	1	Add Pos.1 NEMA 213/215TC, 7.5-10HP (High)	96486311		No
			7-10	1	Add Pos. 1 for NEMA 254/256TC, 15-20HP	96486311		No
			12	1	NEMA, 284/286TSC, 25HP	96486293		No
3	Chamber, Top, Complete with guide vane		2-17	*1	Slotted to accept Strap, pos. 26a	96487786		No
3a	Chamber N, Top, without guide vane		2/1	*1	Slotted to accept Strap, pos. 26a	96491222		No
3b	Chamber without guide vane		3-17	*1		330015		No
4	Chamber complete with Pos. 45 & 65		3-17	^^^	PTFE Pos.45	96475765		No
4a	Chamber N Cpl. w/Pos. 45 & 65 & Bearing		2/1-17	^^^^	Silicon Carbide Brg, PTFE Pos. 45	96747342		YES*
	Chamber N Cpl. w/Pos. 45 & 65 & Brg. (option)		2/1-17	^^^^	Graflon Bearing, PTFE Pos. 45	96492510		YES
	Chamber N Cpl. w/Pos. 45 & 65 & Brg. (option)		2/1-17	^^^^	Bronze Bearing, PTFE Pos. 45	96492512		YES
6	Volute, suction / discharge base		2/1-17	1	GA, 1.5" suction (OD=76mm), 4 hole dis. adapter	95922001		No
	Volute, option larger suction & discharge		2/1-17	1	G05/G22, 2" suction (OD=90mm) 4 hole dis.adapter	95922000		No
			2/1-17	1	GB&C/G10/G50/G60, 3" suc. (OD=120), 6 hole dis. adap.	95922002		No
7	Coupling Guard		2/1	2	NEMA-56C	96491002		YES
7a	Screw for Coupling Guard		2-17	2	NEMA, 182-215TC (High), 254TC-286TSC	96490656		YES
			1-17	4	Screw comb. slot torx/straight slot 4 x 8mm	96488481		YES
9	Allen Screw		2/1	4	M6 x 20mm, Delta Tone/Seal	00ID7899		YES
			2-17	4	M10 x 25mm, Delta Tone/Seal	00ID7901		YES
10	Shaft Pin		2/1-17	1	ø5 x 26mm	310192	95061337	YES
10a	Coupling Half (machined set)		2/1	1	NEMA, 56C, 1/3 - 2HP. ø15.9/ ø16mm	96516777		YES
			2-3	1	NEMA, 182/184TC, 3-5HP. ø28.6/ø16mm (High)	96516009		YES
			4-6	1	NEMA, 213TC, 7.5-10HP. ø34.9/ø16mm (High)	96516770		YES
			7-10	1	NEMA, 254TC, 15-20HP. ø41.2/ø16mm (High)	96516771		YES
			12	1	NEMA, 284/286TSC, 25HP. ø41.2/ø16mm	96516771		YES
12a	Discharge Adapter		2/1-17	1	GA, 4 hole flange, OD= 55mm, ID= 26mm (1.0"), L= 60mm	95922007		No
			2/1-17	1	G05, 4 hole flange, OD= 55mm, ID= 26mm (1.0"), L= 111mm	95922008		No
			2/1-17	1	G22, 4 hole flange, OD= 90mm, ID= 50mm (2"), L= 85mm	95922016		No
	Discharge Adp. option larger suc./dis. & press		2/1-17	1	GB, 6 hole flange, OD= 76mm, ID= 49mm (1.5"), L= 65mm	95922009		No
			2/1-17	1	GC, 6 hole flange, OD= 90mm, ID= 49mm (2"), L= 65mm	95922010		No
			2/1-17	1	G50, 6 hole flange, OD= 76mm, ID= 41mm (1.5"), L= 116mm	95922011		No
			2/1-17	1	G10, 6 hole flange, OD= 90mm, ID= 50mm (2"), L= 110mm	95922012		No
			2/1-17	1	G60, 6 hole flange, OD= 90mm, ID= 50mm (2"), L= 142mm	95922013		No
			2/1-17	1	G20, 6 hole flange, OD= 76mm, ID= 40mm (1.5"), L= 166mm	95922014		No
			2/1-17	1	G30, 6 hole flange, OD= 90mm, ID= 50mm (2"), L= 192mm	95922015		No
			2/1-17	1	G50, 6 hole flange, OD= 76mm, ID= 47mm (1.5"), L= 96mm	96834136		No
			2/1-17	1	G10, 6 hole flange, OD= 90mm, ID= 56mm (2"), L= 90mm	96834137		No
			2/1-17	1	G60, 6 hole, flange, OD= 90mm, ID= 55mm (2"), L= 122mm	96834138		No
			2/1-17	1	G20, 6 hole flange, OD= 76mm, ID= 46mm (1.5"), L= 146mm	96834139		No
			2/1-17	1	G30, 6 hole flange, OD= 90mm, ID= 54mm (2"), L= 172mm	96834140		No
			2/1-17	1	G33, 6 hole flg.OD=120mm, ID= 80mm (3"), L= 110mm	95922017		No
18(a)	Priming/Vent Plug		2/1-17	*	G 1/2A, NV24 with NV9 x M8 stem	405150	95061351	YES
19	(Suction) Pressure tap plug		2/1-17	1	1/4" NPT,SS SQHD	00ID7216		No
19a	(Discharge) Pressure tap plug		2/1-17	1	1/4" NPT,SS SQHD	00ID7216		No
23, 23c	Plug		2/1-17	*	G 1/2A, NV24, solid	370025	95061733	No
25	Drain plug		2/1-17	1	1/4" NPT,SS SQHD	00ID7216		No
26	Staybolt		2/1-2	4	M16 x 150mm	96922785		No
			3	4	M16 x 196mm	96922788		No
			4	4	M16 x 241mm	96922792		No
			5	4	M16 x 286mm	290247		No
			6	4	M16 x 327mm	350179		No
			7	4	M16 x 376mm	96922799		No
			8	4	M16 x 415mm	370134		No
			9	4	M16 x 467mm	96922804		No
			10	4	M16 x 506mm	96922806		No
			12	4	M16 x 596mm	96922810		No
			14	4	M16 x 686mm, 4 pole & 50 Hz.	96922814		No
			17	4	M16 x 827mm, 4 pole & 50 Hz.	370981		No
	Staybolt (Back-to-Back & Tandem Seal option)		2/1-2	4	M16 x 241mm	96922792		No
			3	4	M16 x 286mm	290247		No
			4	4	M16 x 333mm	370133		No
			5	4	M16 x 376mm	96922799		No
			6	4	M16 x 415mm	370134		No
			7	4	M16 x 467mm	96922804		No
			8	4	M16 x 506mm	96922806		No
			9	4	M16 x 550mm	96922808		No
			10	4	M16 x 596mm	96922810		No
			12	4	M16 x 686mm	96922814		No
			14	4	M16 x 776mm, 4 pole & 50 Hz.	290254		No
			17	4	M16 x 916mm, 4 pole & 50 Hz.	290256		No

Due to part changes over time, all position numbers (1-203) may not be used.

This column indicates which pump model uses the spare part. If blank, the part is used in all models.

B.O.M. Ref. No. is only available if it is not included in a kit or does not have a material number listed. If it is included in a kit (YES), or has a material number, request one of these numbers. If not included in a kit (No), but has a Material Number, use Material Number.

Parts List & Kits CR15-H

Pos. No.	Part Description	Model	Stages	No. Used	Comments/Dimensions	B.O.M. Ref. No.	Material No.	Included in kits ?
PARTS LIST								
26a	Strap		2/1-2	2	L* = 93.5mm x 20.3mm x 1.3mm, 316 SS, M8 nut.	96487759		No
			3	2	L* = 138.5mm x 20.3mm x 1.3mm, 316 SS, M8 nut	96487761		No
			4	2	L* = 183.5mm x 20.3mm x 1.3mm, 316 SS, M8 nut	96487763		No
			5	2	L* = 228.5mm x 20.3mm x 1.3mm, 316 SS, M8 nut	96487765		No
			6	2	L* = 273.5mm x 20.3mm x 1.3mm, 316 SS, M8 nut	96487767		No
			7	2	L* = 318.5mm x 20.3mm x 1.3mm, 316 SS, M8 nut	96487769		No
			8	2	L* = 363.5mm x 20.3mm x 1.3mm, 316 SS, M8 nut	96487770		No
			9	2	L* = 408.5mm x 20.3mm x 1.3mm, 316 SS, M8 nut	96487772		No
			10	2	L* = 453.5mm x 20.3mm x 1.3mm, 316 SS, M8 nut	96487774		No
			12	2	L* = 543.5mm x 20.3mm x 1.3mm, 316 SS, M8 nut	96487776		No
			14: 4 pole	2	L* = 633.5mm x 20.3mm x 1.3mm, 316 SS, M8 nut	96487780		No
			17: 4 pole	2	L* = 768.5mm x 20.3mm x 1.3mm, 316 SS, M8 nut	96487782		No
26b	Bolt for Pos. 26a		2/1-17	2	M8 x 25mm, 316 SS w/Delta Tone/Seal	96416603		No
26c	Washer for Pos. 26b		2/1-17	2	A4, Ø16.0/Ø8.4x1.6mm	001D3284		No
28	Motor Bolt		2/1	4	NEMA, 56C, 1/3 - 2HP, UNC 3/8" x 25mm	001D1839		No
			2-3	4	NEMA, 182/184TC, 3 - 5HP, UNC1/2" x 25mm	001D1840		No
			4-6	4	NEMA, 213TC, 7.5 -10HP, JR 1/2" x 1.25" UNC	001D0185		No
			7-10	4	NEMA, 254TC, 15-20HP, 1/2" x 2.5" UNC	96491112		No
			12	4	NEMA, 284TC, 25HP, UNC1/2" x 25mm	001D1840		No
28g	Bolt for Foot 56a & Volute pos. 6 (GA, GB, GC)		2/1-17	2	M12 x 20mm, low hex head, 8.8 Alloy Steel, Delta Tone/Seal	95922047		No
	Bolt - Foot 56a & Volute pos. 6 (G05, G10, G22, G50, G60)		2/1-17	2	M12 x 20mm, 8.8 Alloy Steel, Delta Tone/Seal	95922048		No
35	Bolt for Discharge Adapter Pos. 12a (GB, GC)		2/1-17	6	M12 x 22mm Socket Head Cap Screw, Delta Tone/Seal	95922049		No
	Bolt for Discharge Adapter Pos. 12a (GA, G05)		2/1-17	4	M12 x 25mm Socket Head Cap Screw, Delta Tone/Seal	95922050		No
36	Staybolt Nut		2/1-17	4	24mm x M16, Delta Tone/Seal	001D7908		No
37(b)	Sleeve O-ring		2/1-17	◆◆	EPDM, Ø170.7 x 3.3mm	96483101		YES
			2/1-17	◆◆	FKM, Ø170.7 x 3.3mm	96483102		YES
	Sleeve O-ring (option)		2/1-17	◆◆	FKM, Ø171.25 x 3.3mm	96483109		YES
	Sleeve O-ring (option)		2/1-17	◆◆	FFKM, Ø170.7 x 3.3mm	96483140		YES
39b	O-ring for Discharge Adapter flange Pos. 12a		2/1-17	1	EPDM, Parker 2-238 Ø88.5 x 3.5mm	95922035		YES
			2/1-17	1	FKM, Parker 2-238 Ø88.5 x 3.5mm	95922036		YES
			2/1-17	1	FKM, Parker 2-238 Ø88.5 x 3.5mm	95952037		YES
			2/1-17	1	FFKM, Parker 2-238 Ø88.5 x 3.5mm	95131207		YES
44a	Inlet upper with Pos. 45 & 65		2/1-17	1		96489038		No
44c	Inlet upper with Pos. 45 & 65 (Low NPSH option)		2-17	1		96491227		No
44b	Inlet lower, machined		2/1-17	1		96488000		No
45	Neck Ring		2/1-17	# imp.-	Ø75.8 x Ø59.95 x 1.5mm, PTFE-Acoflon 100	96487400		YES
	Neck Ring (low NPSH option)		2/1-17	1	Ø88.0 x Ø66.2 x 2.2mm, PTFE-Acoflon 215	290091		No
47a	Bearing Ring/Spacer		2/1-17	^^^^	SiC 150, Ø23.4 x Ø17.6 x Ø15.0 x 14mm	96763100		YES
	Brg. Ring/Spacer (option for Graflon / Brz. 4a)		2/1-17	^^^^	TC, Ø21.9 x Ø17.6 x Ø15.0 x 14mm	330085	95061371	YES
49	Impeller		2/1-17	# stgs-	Ø104.8 x Ø59.85 x 25.4mm (back-plate 1.5mm)	96476399		No
49c	Wear Ring N for Impeller 49		2/1-17	# stgs-	Ø59.85 x 7.4mm	330054		YES
49c	Wear Ring N for Low NPSH Impeller 49i		2/1-17	1	Ø66.0 x 8.5mm	290049		No
49i	Impeller N (Low NPSH option)		2-17	1	Ø118.8 x Ø66.0 x 32.2mm	96521444		No
51	Shaft, Complete		2/1-2	1	Ø16 x 209.0mm, 431 SS	96490794		No
			3	1	Ø16 x 249.0mm, 431 SS	96490798		No
			4	1	Ø16 x 299.0mm, 431 SS	96490872		No
			5	1	Ø16 x 339.0mm, 431 SS	96490876		No
			6	1	Ø16 x 389.0mm, 431 SS	96490880		No
			7	1	Ø16 x 429.0mm, 431 SS	96490884		No
			8	1	Ø16 x 479.0mm, 431 SS	96490886		No
			9	1	Ø16 x 519.0mm, 431 SS	96490888		No
			10	1	Ø16 x 564.0mm, 431 SS	96490892		No
			12	1	Ø16 x 659.0mm, 431 SS	96490896		No
			14	1	Ø16 x 744.0mm, 431 SS, 4 pole & 50 Hz.	96490910		No
			17	1	Ø16 x 879.0mm, 431 SS, 4 pole & 50 Hz.	96490915		No
	Shaft, Cpl. (Back-to-Back & Tandem Seal option)		2/1-2	1	Ø16 x 299.0mm, 329 SS	96507538		No
			3	1	Ø16 x 339.0mm, 329 SS	96507570		No
			4	1	Ø16 x 389.0mm, 329 SS	96507572		No
			5	1	Ø16 x 429.0mm, 329 SS	96507574		No
			6	1	Ø16 x 479.0mm, 329 SS	96507576		No
			7	1	Ø16 x 519.0mm, 329 SS	96507578		No
			8	1	Ø16 x 569.0mm, 329 SS	96507579		No
			9	1	Ø16 x 609.0mm, 329 SS	96507580		No
			10	1	Ø16 x 654.0mm, 329 SS	96507582		No
			12	1	Ø16 x 749.0mm, 329 SS	96507584		No
			12	1	Ø16 x 777.0mm, 329 SS (Low NPSH option)	96551867		No
			14	1	Ø16 x 834.0mm, 431 SS, 4 pole & 50 Hz.	96507586		No
			17	1	Ø16 x 969.0mm, 431 SS, 4 pole & 50 Hz.	96507588		No
			17: 4 pole	1	Ø16 x 1014.0mm, 431 SS, Low NPSH & 50 Hz.	96529710		No
55	Sleeve		2/1-2	1	Ø171.1/ Ø170.7 x 104.0mm x 1.5mm, 304 SS	96489762		No
			3	1	Ø171.1/ Ø170.7 x 149.0mm x 1.5mm, 304 SS	96489764		No
			4	1	Ø171.1/ Ø170.7 x 194.0mm x 1.5mm, 304 SS	96489766		No
			5	1	Ø171.1/ Ø170.7 x 239.0mm x 1.5mm, 304 SS	96489767		No

Due to part changes over time, all position numbers (1-203) may not be used.

This column indicates which pump model uses the spare part. If blank, the part is used in all models.

B.O.M. Ref. No. is only available if it is not included in a kit or does not have a material number listed. If it is included in a kit (YES), or has a material number, request one of these numbers. If not included in a kit (No), but has a Material Number, use Material Number.

Parts List & Kits CR15-H

Pos. No.	Part Description	Model	Stages	No. Used	Comments/Dimensions	B.O.M. Ref. No.	Material No.	Included in kits ?
PARTS LIST								
55	Sleeve - continued		6	1	Ø171.1/ Ø170.7 x 284.0mm x 1.5mm, 304 SS	96489769		No
			7	1	Ø171.1/ Ø170.7 x 329.0mm x 1.5mm, 304 SS	96489771		No
			8	1	Ø171.1/ Ø170.7 x 374.0mm x 1.5mm, 304 SS	96489772		No
			9	1	Ø171.1/ Ø170.7 x 419.0mm x 2.0mm, 316 SS	96489857		No
			10	1	Ø171.1/ Ø170.7 x 464.0mm x 2.0mm, 316 SS	96489831		No
			12	1	Ø171.1/ Ø170.7 x 554.0mm x 2.0mm, 316 SS	96489833		No
			14: 4 pole	1	Ø171.1/ Ø170.7 x 644.0mm x 2.0mm, 316 SS	96489835		No
			17: 4 pole	1	Ø171.1/ Ø170.7 x 779.0mm x 2.0mm, 316 SS	96489836		No
55b	Sleeve flange		2/1-17	1	CR-H, CRN-H10, 15, 20, 316 SS.	95131164		No
56a	Foot (Cast Iron) for Pos. 6 (GA, GB, GC)		2/1-17	1	H= 21mm, W= 198mm, Ø16mm hole CL 142mm, Cl.	95922023		No
	Foot (Cast Iron) for Pos. 6 (G05, G10, G22, G50, G60)		2/1-17	1	H= 98mm, W= 300mm, Ø16mm hole CL 248mm, Cl.	95922024		No
	Foot (Cast Iron) for Pos. 6 (C1, G20, G30)	254TC	2/1-17	1	H= 142mm, W= 300mm, Ø16mm hole CL 248mm, Cl.	96834143		No
56b(d)	Washer for bolt Pos. 56c		2/1-17	16	M12, 304 SS	00ID3103		No
56c	Bolt for sleeve flange Pos. 55b		2/1-17	8	M12x1.75 x60mm, 12.9 Alloy Steel, Delta Tone/Seal	97672735		No
56e	Nut for bolt Pos. 56c		2/1-17	8	M12, NV19, 8.8 Steel, Delta Tone/Seal	00ID7917		No
56f	Bolt for Pos. 90 (BP139 w/GA, BP245 G05/22)	56/182T	2/1-2	2	Hex Hd.1/2 -13 UNC x 1" SAE 5, Zinc plated			YES
	Bolt for Pos. 90 (BP258 G05/22)	254/84TC	6-12	2	Hex Hd.1/2 -13 UNC x 1" SAE 5, Zinc plated			YES
	Bolt for Pos. 90 (BP148 w/GA, GB, BP252 G05/22)	213TC	3-5	2	Hex Head 1/2 -13 UNC x 1.25" SAE 5, Zinc plated			YES
	Bolt for Pos. 90 (XLBP4 w/GA, GB)	284TC	12	2	Hex Head 1/2 -13 UNC x 1.25" SAE 5, Zinc plated			YES
	Bolt for Pos. 90 (BP148 with GA/GB, Pos. 56k & m)	254TC	6-10	2	Hex Head 1/2 -13 UNC x 2.25" SAE 5, Zinc plated			YES
56g	Washer for bolt Pos. 56f		2/1-17	2	1/2" SAE, Zinc plated			YES
56k	Spacer for base Pos. 90	GA/GB	6-10	1	148BP 254T, L=200mm x H=25.4mm x W=78.2mm			YES
56m	Alignment pin	GA/GB	6-10	2	Slotted Spring Pin, Ø3/16" x 1" ASME, Zinc plated			YES
60	Stack Compression Spring		2/1-17	4	Ø11.0 x Ø7.0 x 15.5mm, EPDM	96503070		YES
			2/1-17	4	Ø11.0 x Ø7.0 x 15.5mm, FKM	96503072		YES
60a	Stack Compression Spring (option)		2/1-17	4	Ø11.0 x Ø7.0 x 15.5mm, PTFE	96503071		YES
61	Stop spacer		2/1-17	1	Ø22.0 x Ø17.8 x Ø15.11 x 11.8 x 6.8mm	96783511		YES
64	Spacing Pipe		3-17	^^^	Ø21.5 x Ø17.5 x 43.6mm	331407		No
64a	Spacing Pipe		2-17	^^^^	Ø21.5 x Ø17.5 x 17.0mm	331416		YES
64b	Spacing Pipe		2-17	^^^^	Ø21.5 x Ø17.5 x 5.0mm	331401		YES
64c	Clamp, Splined		2/1-17	1	Ø21.5 x Ø17.6 x Ø15.0 x 12.7mm	96496311		YES
64d	Spacing Pipe		2/1-17	^^^^^^	Ø21.5 x Ø17.5 x 12.6mm	96491535		YES
64e	Spacing Pipe (Low NPSH option only)		2-17	^ +	Ø21.5 x Ø17.5 x 8.0mm	331411		No
64f	Spacing Pipe (Low NPSH option only)		2/1	^ -	Ø21.5 x Ø17.5 x 18.0mm	96491536		No
64g	Spacing Pipe (de-staging 2 impellers option only)		3-17	1 per de-stg	Ø21.5 x Ø17.5 x 45.0mm (use with 3b only)	331408		No
65	Neck Ring Retainer		2/1-17	# stgs-1	Ø78.8 x Ø61.5 x 6.7mm	330059	96547341	YES
	Neck Ring Retainer (Low NPSH option)		2-17	1	Ø84.5 x Ø67.8 x 4.6mm	290059		YES
66	Lock Washer Set for Shaft		2/1-17	1	Ø13.5 x Ø8.2 x 2.6mm	96417297		YES
66a	Washer for Staybolt		2/1-17	4	DIN 125A, Ø30 x Ø17 x 2.5mm, Delta Tone/Seal	96430378		No
67	Lock Nut for Shaft		2/1-17	1	13mm x M8	96496488		YES
69	Spacing Pipe		2-17	⊖	Ø27.5 x Ø17.5 x 27.5mm	96491537		No
69a	Spacing Pipe (de-staging option only)		2/1	1	Ø21.5 x Ø17.5 x 29.05mm (use with 3a only)	331404	95061499	No
72a	O-ring for Sleeve Flange Pos. 55b		2/1-17	1	EPDM, Ø215.5mm	95922038		YES
			2/1-17	1	FKM, Ø215.5mm	95922039		YES
			2/1-17	1	FFKM, Ø215.5mm	95131208		YES
			2/1-17	1	FKM, Ø215.5mm	95922040		YES
76	Nameplate		2/1-17	1	304SS, 60 x 45mm	96563333		No
76a	Rivet for Nameplate		2/1-17	2	304SS, Ø3 x 5mm	96022882		No
77a	Pump Head Cover for Tandem Seal & Cool Top®		2/1-17	1	Cast Stainless	96505487		No
	Pump Head Cover for Back-to-Back		2/1-17	1	Cast Stainless	96505488		No
79a	Disc / Plate complete w/79b & c for Cool Top		2/1-17	1	Cast Stainless	96511281		No
79b	Bushing for Disc / Plate 79a		2/1-17	1	Graflon	96505571		No
79c	Retaining Ring for 79b		2/1-17	1	Stainless	96510985		No
90	Main Support Baseplate	GA/GB	2/1-2	1	BP. Cpl. 139, L=991mm x W=305mm x H=106.5mm	96956336		YES
		GA/GB	3-6	1	BP. Cpl. 148, L=1219mm x W=381mm x H=107.9mm	96956346		YES
		G05/22	2/1-2	1	BP. Cpl. 245, L=1143mm x W=305mm x H=106.5mm	96956341		YES
		G05/22	3-5	1	BP. Cpl. 252, L=1320.8mm x W=381mm x H=107.9mm	96956356		YES
		G05/22	6-10	1	BP. Cpl. 258, L=1473.2mm x W=457.2mm x H=119.1mm	96956360		YES
	Main Support Baseplate - Longer versions	GA/GB		1	XLBP1(139/245), L=1500mm x W=381mm6.5=106.5mm	96956376		YES
		GA/GB	7-10	1	XLBP2(148/252), L=1777.8mm x W=381mm x H=107.9mm	96956377		YES
		G22	12	1	XLBP3(258/264), L=2406.4mm x W=457.2mm x H=119.1mm	96956379		YES
		GA/GB	12	1	XLBP4(153), L=2406.4mm x W=457.2mm x H=194mm	96957102		YES
90a	Bolt for motor to slider Pos. 90b	56C	2/1	4	Hex Head 5/16 -18 UNC x .75" SAE 5, Zinc plated			YES
		182TC	2	4	Hex Head 3/8 -16 UNC x .5" SAE 5, Zinc plated			YES
		213TC	3-5	4	Hex Head 3/8 -16 UNC x 5/8" SAE 5, Zinc plated for GA/GB			YES
		213TC	3-5	4	Hex Head 3/8 -16 UNC x 1" SAE 5, Zinc plated for G05/22			YES
		254-284	6-12	4	Hex Head 1/2 -13 UNC x 1.25" SAE 5, Z.P. for G05/22			YES
		254-284	6-12	4	Hex Head 1/2 -13 UNC x 1.5" SAE 5, Zinc plated for GA/GB			YES

Due to part changes over time, all position numbers (1-203) may not be used.

This column indicates which pump model uses the spare part. If blank, the part is used in all models.

B.O.M. Ref. No. is only available if it is not included in a kit or does not have a material number listed. If it is included in a kit (YES), or has a material number, request one of these numbers. If not included in a kit (No), but has a Material Number, use Material Number.

Parts List & Kits CR15-H

Pos. No.	Part Description	Model	Stages	No. Used	Comments/Dimensions	B.O.M. Ref. No.	Material No.	Included in kits ?
PARTS LIST								
90b	Motor support / slider	56C	2/1	2	GA,GB,GC, BP139, L=204mm x H=45.5mm x W=25.4mm	96956339		YES
		182TC	2	2	GA,GB,GC, BP139, L=230mm x H=23mm x W=25.4mm	96956338		YES
		213TC	3-5	2	GA,GB,GC, BP148, L=252mm x H=20mm x W=25.4mm	96956347		YES
		254TC	6-10	2	GA,GB,GC, BP148, L=299mm x H=20.3mm x W=25.4mm	96956348		YES
		284TC	12	2	GA,GB,GC, BP153, L=366mm x H=46mm x W=25.4mm	96956351		YES
		56C	2/1	2	G05, G22, BP245, L=204mm x H=125.5mm x W=25.4mm	96956343		YES
		182TC	2	2	G05, G22, BP245, L=230mm x H=100mm x W=25.4mm	96956342		YES
		213TC	3-5	2	G05, G22, BP252, L=252mm x H=96.5mm x W=25.4mm	96956357		YES
		254TC	6-10	2	G05, G22, BP252, L=354mm x H=67mm x W=25.4mm	96956361		YES
		284TC	12	2	G05, G22, BP258, L=354mm x H=67mm x W=25.4mm	96956361		YES
90c	Support Bracket for Pump Cartridge		2/1-17	1	304 SS, H=59mm CL of hole, GA/GB/GC	95131178		No
			2/1-17	1	304 SS, H=136mm CL of hole, G05/G10/G22/G50/G60	95131180		No
			2/1-17	1	304 SS, H=180mm CL of hole, G20/G30	96834148		No
90d	Bolt for motor slider Pos. 90b to base Pos. 90	56C	2/1	4	Hex Head 1/4 -20 UNC x 1" SAE 5, Zinc plated			YES
		182/213	2-5	4	Hex Head 1/4 -20 UNC x 1.75" SAE 5, Z.P. for GA/GB			YES
		213-284	3-12	4	Hex Head 1/4 -20 UNC x 1.75" SAE 5, Z.P. for G05/G22			YES
		284TC	12	4	Hex Head 1/4 -20 UNC x 2.25" SAE 5, Z.P. for GA/GB			YES
		254TC	6-10	4	Hex Head 1/4 -20 UNC x 2.5" SAE 5, Z.P. for GA/GB			YES
		182TC	2	4	Hex Head 1/4 -20 UNC x 2.5" SAE 5, Z.P. for G05/G22			YES
90f	Washer for motor bolt pos. 90a to slider pos. 90b	56C	2/1	4	5/16" SAE, Zinc plated			YES
		182/213	2-5	4	3/8" SAE, Zinc plated			YES
		254-284	6-12	4	1/2" SAE, Zinc plated			YES
100	Priming/Vent Plug O-ring		2/1-17	■	EPDM, Ø16.3 x 2.4mm	00ID1288		YES
100a	Priming/Vent Plug O-ring (option)		2/1-17	■	FKM, Ø16.3 x 2.4mm	00ID2231		YES
			2/1-17	■	FFKM, Ø16.3 x 2.4mm	96428162	96587720	YES
105(b)	Priming/Vent Plug O-ring (option)		2/1-17	■	FXM, Ø16.3 x 2.4mm	96442869	96587721	YES
	Shaft Seal HQBE		2/1-17	***	SiC, Carbon with resin-impregnated, EPDM	96484076		YES
	Shaft Seal HQBV		2/1-17	***	SiC, Carbon with resin-impregnated, FKM	96484077		YES
	Shaft Seal HQQE		2/1-17	***	SiC, SiC, EPDM	96484071		YES
	Shaft Seal HQQV		2/1-17	***	SiC, SiC, FKM	96484072		YES
	Shaft Seal HQQF (option)		2/1-17	***	SiC, SiC, FXM	96484075		YES
	Shaft Seal HQQK (option)		2/1-17	***	SiC, SiC, FFKM	96484074		YES
	Shaft Seal HUBE		2/1-17	***	TC, Carbon with resin-impregnated, EPDM	96483952		YES
	Shaft Seal HUBV		2/1-17	***	TC, Carbon with resin-impregnated, FKM	96483964		YES
	Shaft Seal HUBF (option)		2/1-17	***	TC, Carbon with resin-impregnated, FXM	96483966		YES
	Shaft Seal HUBK (option)		2/1-17	***	TC, Carbon with resin-impregnated, FFKM	96483965		YES
	Shaft Seal HUUE		2/1-17	***	TC, TC, EPDM	96483967		YES
	Shaft Seal HUUV		2/1-17	***	TC, TC, FKM	96483968		YES
	Shaft Seal HUUF (option)		2/1-17	***	TC, TC, FXM	96484070		YES
	Shaft Seal HUUK (option)		2/1-17	***	TC, TC, FFKM	96483969		YES
117	Pipe for Air Vent 118		2/1-17	1	G1/2, 316SS	96525189		YES
117a	Counter Nut for Pipe 117		2/1-17	2	NV24, internal G1/2, 316SS	96506709		YES
118	Air Vent		2/1-17	1	Air vent type 1511-AV - 5/6430	96427483		YES
201	Flange, Suction		2/1-7	1	1.5" 150#, 4 x 1/2"-13 UNC threaded flange, e-coat	96922828		No
			2/1-7	1	2" 150#, 4 x 5/8"-11 UNC threaded flange, e-coat	96922829		No
			2/1-7	1	3" 150#, 8 x non thread flange, electrocoated	350085		No
			8-17	1	1.5" 300#, 4 x 3/4"-10 UNC threaded flange, e-coat	96956145		No
			8-17	1	2" 300#, 8 x 5/8"-11 UNC threaded flange, e-coat	96956146		No
			8-17	1	3" 300#, 8 x 3/4"-10 UNC threaded flange, e-coat	96956147		No
			2/1-7	1	1" 150#, 4 x 1/2"-13 UNC threaded flange, e-coat	96922827		No
			2/1-7	1	1.5" 150#, 4 x 1/2"-13 UNC threaded flange, e-coat	96922828		No
			2/1-7	1	2" 150#, 4 x 5/8"-11 UNC threaded flange, e-coat	96922829		No
			8-17	1	1" 300#, 4 x 5/8"-11 UNC threaded flange, e-coat	96956144		No
201a	Flange, Discharge		8-17	1	1.5" 300#, 4 x 3/4"-10 UNC threaded flange, e-coat	96956145		No
			8-17	1	2" 300#, 8 x 5/8"-11 UNC threaded flange, e-coat	96956146		No
			8-17	1	3" 300#, 8 x 3/4"-10 UNC threaded flange, e-coat	96956147		No
			2/1-7	1	1" 150#, 4 x 1/2"-13 UNC threaded flange, e-coat	96922827		No
			2/1-7	1	1.5" 150#, 4 x 1/2"-13 UNC threaded flange, e-coat	96922828		No
203	Retaining ring for 201, 1.5" flange		2/1-17	1	Ø72.6mm x 5mm	96475395	96547671	No
			2/1-17	1	Ø86.6mm x 5mm	96475396		No
			2/1-17	1	Ø121mm x 6mm	350009		No
203a	Retaining ring for 201a, 1.0" flange		2/1-17	1	Ø53.6mm x 3.2mm	96439718		No
			2/1-17	1	Ø72.6mm x 5mm	96475395	96547671	No
			2/1-17	1	Ø86.6mm x 5mm	96475396		No
			2/1-17	1	Ø121mm x 6mm	350009		No

Due to part changes over time, all position numbers (1-203) may not be used.

This column indicates which pump model uses the spare part. If blank, the part is used in all models.

B.O.M. Ref. No. is only available if it is not included in a kit or does not have a material number listed. If it is included in a kit (YES), or has a material number, request one of these numbers. If not included in a kit (No), but has a Material Number, use Material Number.

NOTES:

The first number is total number of impellers.
An exceptions to this format is the CR15-1.

Example: A CR15-1 is actually a CR15-2/1. It has 2 chambers and 1 impeller (de-staged by 1), and uses a 2 stage shaft.

YES* If the YES is followed by an asterisk, the part in kit is made of upgraded material (example 304 SS changed to 316 SS for Pos. 4a)

* 1 2 to 17 stage use Pos. 3
2 /1 stage use Pos. 3a
De-staging by two impellers use one 3a and one 3b

^^^ 2/1 and 2 stage = use 0
3 to 6 stage = # of stages less 2
7 to 10 stage = # of stages less 3
12 to 17 stage = # of stages less 4
De-staging by two impellers use 1 less than stated above.

^^^^ 2/1 to 6 stage = use 1
7 to 10 stage = use 2
12 to 17 stage = use 3

^^^^^ 2/1-2, 4, 6, 8, and 12 stage = use 1
Exception to the above: Low NPSH models

2, 4, 6, 8, 9 to 17 stage = use 1
3, 5 and 7 stage = use 2

^^^^^^ 2/1 to 6 stage = use 1
7 to 10 stage = use 2
12 to 17 stage = use 3
Exception to the above: Low NPSH models

2 to 6 stage = use 0
7 to 10 stage = use 1
12 to 17 stage = use 2

^ + NPSH Models only
3, 6, 8, 9, & 17 stage = use 1
2, 4, 6, 10, 12 & 14 stage = use 2

^ - NPSH Models only
3, 6, 8, 9, & 17 stage = use 1

* Standard use 1. Back-to-Back or Tandem pump version use 2

** Standard use 1. Back-to-Back or Tandem pump version use 2

*** Standard use 1. Back-to-Back or Tandem pump version use 2

⊖ Standard use 1. CR(I,N)15-2/1 replace with Pos. 69a

stgs- Use the number of stages in standard models,
less one in de-staged and Low NPSH models.

imp.- Use the number of stages in standard models,
less one in de-staged and Low NPSH models.

◆◆ Standard use 2. Back-to-Back or Tandem pump version use 3,
Cool Top use 1 EPDM or FKM and 2 FXM in lower hot section of pump.

■ Standard use 2. Back-to-Back or Tandem pump version use 6

L* Is a tip-to-tip length which includes the bends for slot engagement.
Bottom tip to bend is 4.5mm shorter than the tip-to-tip value.

Key to Symbols

KITS		Recommended spare part
Ø		Diameter
ANSI		American National Standards Institute
CPL		Complete Assembly – these parts consist of more than one component
EPDM		Ethylene Propylene (also known as EPR and EPT) – an elastic substance similar to rubber
FFKM		Kalrez Elastomer made by DuPont
FKM		Fluoro Elastomer (generic for Viton)
FXM		Fluoraz Elastomer made by Greene Tweed
IEC		International Electro-technical Commission (European standards)
M		International standard thread size designation (thread diameter in mm)
mm		Millimeter
MG		Identifies Grundfos motor type/size
N		Stamp code for 316 SS or similar
NBR		Buna - N (also known as Nitrile) – an elastic substance similar to rubber
NEMA		National Electrical Manufacturers Association
NPSH		Net Positive Suction Head
PTFE		Teflon
SiC		Silicon Carbide
SS		Stainless Steel
TC		Tungsten Carbide
UNC		Unified National Coarse – a standard for threads on bolts

Spare Part Kits CR15-H

SPARE PART KITS

Since certain pump parts can be expected to exhibit wear at the same time as related pump parts, they have been grouped into the following kits for your convenience. The numbers indicate the quantity of the part within each kit. Please order these kits using the kit material number at the top of the columns.

CR(I, N)15 SiC Bearing					
WEAR PARTS KIT 1-6			Kit No.		96511824
WEAR PARTS KIT 7-10			Kit No.		96511827
WEAR PARTS KIT 12-17			Kit No.		96511830
Pos. No.	Description	Material No.	Qty. Included in each Kit		
4a	Chamber N Cpl. w/Pos.45 & 65 & SiC Bearing	96747343	1	2	3
26b	Bolt for strap, M8 x 25mm, 316 SS w/Delta Seal	96416603	2	2	2
26c	Washer for strap, A4, Ø16.0/Ø8.4x1.6mm	00ID3284	2	2	2
45	Neck Ring, Ø75.8 x Ø59.95 x 1.5mm, PTFE-Acoflon 100	96487400	5	8	14
47a	Bearing Ring/Spacer, SiC 150, Ø23.4 x 14mm	96763100	1	2	3
49c	Wear Ring, N, Ø59.85 x 7.4mm	330054	6	10	17
61	Stop Spacer, Ø29.0 x Ø18.4 x Ø17.6 x Ø15.0 x 9.5 x 2mm	330072	1	1	1
62	Stop Ring, Ø16.6 x Ø15.0 x 1.6mm	330057	1	1	1
64a	Spacing Pipe, Ø21.5 x Ø17.5 x 17.0mm	331416	1	2	3
64b	Clamp, Splined, Ø21.5 x Ø17.6 x Ø15.0 x 5.0mm	331401	1	1	1
64c	Clamp, Splined, Ø21.5 x Ø17.6 x Ø15.0 x 12.7mm	96496311	1	1	1
64d	Spacing Pipe, Ø21.5 x Ø17.5 x 12.6mm	96491535	1	2	3
65	Neck Ring Retainer, N, Ø78.8 x Ø61.5 x 6.7mm	330059	5	8	14
66	Lock Washer Set of 2, Ø13.5 x Ø8.2 x 2.6mm	96417297	1	1	1
67	Lock Nut. 13mm x M8	96496488	1	1	1

STACK KITS (SIC) Pos.80	
Model	Material No.
CR15-2/1	96491736
CR15-2	96491737
CR15-3	96491738
CR15-4	96491739
CR15-5	96491740
CR15-6	96491741
CR15-7	96491742
CR15-8	96491743
CR15-9	96491744
CR15-10	96491745
CR15-12	96491746
*** CR15-14	96491747
*** CR15-17	96491748

***For 4 pole & 50 Hz. operation only.

CR(I, N)15 Grafion Bearing					
WEAR PARTS KIT 1-6			Kit No. 96511826		
WEAR PARTS KIT 7-10			Kit No. 96511829		
WEAR PARTS KIT 12-17			Kit No. 96511832		
Pos. No.	Description	Material No.	Qty. Included in each Kit		
4a	Chamber N Cpl. w/Pos.45 & 65 & Grafion Bearing	96492510	1	2	3
26b	Bolt for strap, M8 x 25mm, 316 SS w/Delta Seal	96416603	2	2	2
26c	Washer for strap, A4, ø16.0/ø8.4x1.6mm	00ID3284	2	2	2
45	Neck Ring, ø75.8 x ø59.95 x 1.5mm, PTFE-Acoflon 100	96487400	5	8	14
47a	Bearing Ring/Spacer, TC, ø21.9 x ø17.6 x ø15.0 x 14mm	330085	1	2	3
49c	Wear Ring, N, ø59.85 x 7.4mm	330054	6	10	17
61	Stop Spacer, ø29.0 x ø18.4 x ø17.6 x ø15.0 x 9.5 x 2mm	330072	1	1	1
62	Stop Ring, ø16.6 x ø15.0 x 1.6mm	330057	1	1	1
64a	Spacing Pipe, ø21.5 x ø17.5 x 17.0mm	331416	1	2	3
64b	Clamp, Splined, ø21.5 x ø17.6 x ø15.0 x 5.0mm	331401	1	1	1
64c	Clamp, Splined, ø21.5 x ø17.6 x ø15.0 x 12.7mm	96496311	1	1	1
64d	Spacing Pipe, ø21.5 x ø17.5 x 12.6mm	96491535	1	2	3
65	Neck Ring Retainer, N, ø78.8 x ø61.5 x 6.7mm	330059	5	8	14
66	Lock Washer Set of 2, ø13.5 x ø8.2 x 2.6mm	96417297	1	1	1
67	Lock Nut. 13mm x M8	96496488	1	1	1

CR(I, N)15 Bronze Bearing						
WEAR PARTS KIT 1-6		Kit No.		96511825		
WEAR PARTS KIT 7-10		Kit No.		96511828		
WEAR PARTS KIT 12-17		Kit No.		96511831		
Pos. No.	Description	Material No.	Qty. Included in each Kit			
4a	Chamber N Cpl. w/Pos.45 & 65 & Bronze Bearing	96492512	1	2	3	
26b	Bolt for strap, M8 x 25mm, 316 SS w/Delta Seal	96416603	2	2	2	
26c	Washer for strap, A4, ø16.0/ø8.4x1.6mm	00ID3284	2	2	2	
45	Neck Ring, ø75.8 x ø59.95 x 1.5mm, PTFE-Acoflon 100	96487400	5	8	14	
47a	Bearing Ring/Spacer, TC, ø21.9 x ø17.6 x ø15.0 x 14mm	330085	1	2	3	
49c	Wear Ring, N, ø59.85 x 7.4mm	330054	6	10	17	
61	Stop Spacer,ø29.0 x ø18.4 x ø17.6 x ø15.0 x 9.5 x 2mm	330072	1	1	1	
62	Stop Ring, ø16.6 x ø15.0 x 1.6mm	330057	1	1	1	
64a	Spacing Pipe, ø21.5 x ø17.5 x 17.0mm	331416	1	2	3	
64b	Clamp, Splined, ø21.5 x ø17.6 x ø15.0 x 5.0mm	331401	1	1	1	
64c	Clamp, Splined, ø21.5 x ø17.6 x ø15.0 x 12.7mm	96496311	1	1	1	
64d	Spacing Pipe, ø21.5 x ø17.5 x 12.6mm	96491535	1	2	3	
65	Neck Ring Retainer, N, ø78.8 x ø61.5 x 6.7mm	330059	5	8	14	
66	Lock Washer Set of 2, ø13.5 x ø8.2 x 2.6mm	96417297	1	1	1	
67	Lock Nut, 13mm x M8	96496488	1	1	1	

HQxx SHAFT SEAL KIT, BALANCED CARTRIDGE (Maximum allowed working PSI is 435) (Tandem Seal option Pumps require 2 of each Seal Kit)			Kit No. 96511848					
			Kit No. 96511849					
			Kit No. 96511844					
			Kit No. 96511847					
			Kit No. 96511846					
			Kit No. 96511845					
Pos. No.	Description	Material No.	Qty. Included in each Kit					
105	HQBE	96484076*	1					
	HQBV	96484077*		1				
	HQQE	96484071*			1			
	HQQF	96484075*				1		
	HQQK	96484074*					1	
	HQQV	96484072*						1
N/A	Grinding Device Tool for Emery Cloth	370711	1	1	1	1	1	1
N/A	Emery Cloth	370712	1	1	1	1	1	1

* Seal material number includes the Adjusting fork 96483950.

SPARE PART KITS (Continued)

HUxx SHAFT SEAL KIT, BALANCED CARTRIDGE (Maximum allowed working PSI is 435)			Kit No. 96511836							
			Kit No. 96511839							
			Kit No. 96511838							
			Kit No. 96511837							
			Kit No. 96511840							
			Kit No. 96511843							
			Kit No. 96511842							
			Kit No. 96511841							
Pos. No.	Description	Material No.	Qty. Included in each Kit							
105	HUBE	96483952*	1							
	HUBF	96483966*		1						
	HUBK	96483965*			1					
	HUBV	96483964*				1				
	HUUE	96483967*					1			
	HUUF	96484070*						1		
	HUUK	96483969*							1	
	HUUV	96483968*								1
N/A	Grinding Device Tool for Emery Cloth	370711	1	1	1	1	1	1	1	1
N/A	Emery Cloth	370712	1	1	1	1	1	1	1	1

* Seal material number includes the Adjusting fork 96483950.

Standard CR Gasket Kits

GASKET KIT (EPDM)			Kit No. 96509609							
GASKET KIT (FKM)			Kit No. 96509610							
GASKET KIT (FKM)			Kit No. 96534871							
GASKET KIT (FFKM)			Kit No. 96533374							
GASKET KIT (EPDM)-Double Seal option.			Kit No. 96525433							
GASKET KIT (FKM)-Double Seal option.			Kit No. 96525434							
GASKET KIT (FKM/EPDM)-Double Seal option.			Kit No. 96525435							
GASKET KIT (FFKM/FFKM)-Double Seal option.			Kit No. 96525436							
GASKET KIT (FKM/EPDM)-Cool Top option.			Kit No. 96525432							
Pos. No.	Description	Material No.	Qty. Included in each Kit							
37	Sleeve O-ring, EPDM (WRC NSF), $\phi 170.7 \times 3.3$ mm	96483101	2				3		1	1
	Sleeve O-ring, FKM, $\phi 170.7 \times 3.3$ mm	96483102		2				3		1
37b	Sleeve O-ring, FKM, $\phi 171.25 \times 3.3$ mm	96483109			2				2	2
	Sleeve O-ring, FFKM, $\phi 170.7 \times 3.3$ mm	96483140				2				
37c	Disc Plate O-ring, EPDM, $\phi 155.0 \times 3.0$ mm	96509703								1
	Disc Plate O-ring, FKM, $\phi 155.0 \times 3.0$ mm	96480168								
38, 100(a,b)	Drain Plug O-ring, EPDM, $\phi 16.3 \times 2.4$ mm	00ID1288	3				7		4	1
	Drain Plug O-ring, FKM, $\phi 16.3 \times 2.4$ mm	00ID2231		3				7		4
	Drain Plug O-ring, FKM, $\phi 16.3 \times 2.4$ mm	96442869			3					3
	Drain Plug O-ring, FFKM, $\phi 16.3 \times 2.4$ mm	96428162				3			3	
38a	Drain Plug O-ring, EPDM, $\phi 5.3 \times 2.4$ mm	00ID2142	1				1			
	Drain Plug O-ring, FKM, $\phi 5.3 \times 2.4$ mm	00ID3945						1		
	Drain Plug O-ring, FKM, $\phi 5.3 \times 2.4$ mm	96511292			1					1
	Drain Plug O-ring, FFKM, $\phi 5.3 \times 2.4$ mm	96511293				1			1	
39	Flange O-ring, EPDM, $\phi 90 \times 3$ mm	96496200	2				2			
	Flange O-ring, FKM, $\phi 90 \times 3$ mm	00ID2856		2				2		
	Flange gasket, Fiber, 122mm x $\phi 60 \times \phi 44 \times 2$ mm	420039	2	2			2	2	2	2
	Flange gasket, Fiber, $\phi 102 \times \phi 65 \times 2$ mm	330035	2	2	2	2	2	2	2	2
	Flange gasket, Fiber, $\phi 92 \times \phi 49 \times 2$ mm	00ID2582	2	2	2	2	2	2	2	2
60(a)	Stack Compression Spring, EPDM, $\phi 11.0 \times \phi 7.0 \times 15.5$ mm	96503070	4				4			4
	Stack Compression Spring, FKM, $\phi 11.0 \times \phi 7.0 \times 15.5$ mm	96503072		4				4		
	Stack Compression Spring, PTFE, $\phi 11.0 \times \phi 7.0 \times 15.5$ mm	96503071			4	4			4	4
109a	Disc Plate O-ring, EPDM, $\phi 27.5 \times 2.75$ mm	96483103								
	Disc Plate O-ring, FKM, $\phi 27.5 \times 2.75$ mm	96483104								
	Disc Plate O-ring, FKM, $\phi 27.5 \times 2.75$ mm	96483141								1

Add to above standard gaskets to complete desired CRH, CRNH model

Kit, O-ring EPDM CR-H, CRN-H10/15/20/32 GA/G05/G22			Kit No. 96922800							
Kit, O-ring FKM CR-H, CRN-H10/15/20/32 GA/G05/G22			Kit No. 96922802							
Kit, O-ring FFKM CR-H, CRN-H10/15/20/32 GA/G05/G22			Kit No. 96922816							
Kit, O-ring EPDM CR-H, CRN-H10/15/20/32 GB-G60			Kit No. 96922822							
Kit, O-ring FKM CR-H, CRN-H10/15/20/32 GB-G60			Kit No. 96956134							
Kit, O-ring FFKM CR-H, CRN-H10/15/20/32 GB-G60			Kit No. 96956135							
Kit, O-ring FKM CR-H, CRN-H10/15/20/32 GB-G60			Kit No. 96923565							
Kit, O-ring FFKM CR-H, CRN-H10/15/20/32 GB-G60			Kit No. 96923571							
Pos. No.	Description	Material No.	Qty. Included in each Kit							
72a	O-ring, 2-268 EPDM $\phi 215.5 \times 3.5$ mm	95922038	1				1			
	O-ring, 2-268 Viton $\phi 215.5 \times 3.5$ mm	95922039		1				1		
	O-ring, 2-268 Fluoraz $\phi 215.5 \times 3.5$ mm	95922040			1				1	
	O-ring, 2-268 FFKM $\phi 215.5 \times 3.5$ mm	95131208				1				1
39b	O-ring, 2-230 EPDM $\phi 63.1 \times 3.5$ mm	95922032	1							
	O-ring, 2-230 Viton $\phi 63.1 \times 3.5$ mm	95922033		1						
	O-ring, 2-230 Fluoraz $\phi 63.1 \times 3.5$ mm	95922034			1					
	O-ring, 2-230 FFKM $\phi 63.1 \times 3.5$ mm	95131189				1				
	O-ring, Parker 2-238 EPDM $\phi 88.5 \times 3.5$ mm	95922035					1			
	O-ring, 2-238 Viton $\phi 88.5 \times 3.5$ mm	95922036						1		
	O-ring, 2-238 Fluoraz $\phi 88.5 \times 3.5$ mm	95952037							1	
	O-ring, 2-238 FFKM $\phi 88.5 \times 3.5$ mm	95131207								1

NEMA COUPLING KIT

$\phi 15.9/\phi 16$			Kit No. 96511353							
$\phi 28.6/\phi 16$ (Option- High)			Kit No. 96753660							
$\phi 34.9/\phi 16$ (Option- High)			Kit No. 96753661							
$\phi 41.3/\phi 16$			Kit No. 96511356							
Pos. No.	Description	Material No.	Qty. Included in each Kit							
9	Allen Screw, M6 x 20mm, Delta Seal	00ID7899	4							
	Allen Screw, M10 x 25mm, Delta Seal	00ID7901		4				4		
10	Shaft Pin, $\phi 5 \times 26$ mm, Stainless	310192	1	1				1		1
10a	Coupling, Half set, 56C, 1/3 - 2HP, $\phi 15.8 / \phi 16$	96516777	1							
	Cplg. Half set, 182/184TC, 3-SHP, High, $\phi 28.5/\phi 16$	96516009		1						
	Cplg. Half set, 213TC, 7.5-10HP, High, $\phi 34.9/\phi 16$	96516770			1					
	Cplg. Half set, 254TC-284/286TSC 15-25HP, $\phi 41.2/\phi 16$	96516771				1				
N/A	Adjusting Fork	96483950	1							1

Spare Part Kits CR15-H

SPARE PART KITS (Continued)

COUPLING GUARD KIT		Kit No. 96509612	
NEMA 56C, 1/3-2HP		Kit No. 96509614	
Pos. No.	Description	Material No.	Qty. Included in each Kit
7	Coupling Guard, W=127mm x H=90.5mm	96491002	2
	Coupling Guard, W=157mm x H=171mm	96490656	2
7a	Screw comb.slot torx/straight slot 4 x 8mm	96488481	4

Air Vent Kit - Horizontal Units		Kit No. 91136720	
CR-H, CRN-H15 to 20			
Pos. No.	Description	Material No.	Qty. Included in each Kit
117	Air Vent Pipe, short for 118, G1/2, 60x43	96525189	1
117a	Counter Nut for Pipe 117, G1/2	96506709	2
118	Air vent type 1511-AV - 5/6430	96427483	1

ANSI COMPANION FLANGES FOR MEDIUM CR-H					
Kit No. 97642565 1.5" x 1" CI BLACK for GA 125#		1.5"		1"	
Pos. No.	Description	Material No.	Qty.	Material No.	Qty.
N/A	Bolts	97693886	4	97693886	4
N/A	Flanges	91123167	1	96983489	1
N/A	Gasket	91123168	1	97692916	1
Kit No. 96967594 1.5" x 1" CI BLACK for GA 250#		1.5"		1"	
Pos. No.	Description	Material No.	Qty.	Material No.	Qty.
N/A	Bolts	91137423	4	91130816	4
N/A	Flanges	96983494	1	96983493	1
N/A	Gasket	97694408	1	97694407	1
Kit No. 97642567 2" x 1" CI BLACK for G05 125#		2"		1"	
Pos. No.	Description	Material No.	Qty.	Material No.	Qty.
N/A	Bolts	91130816	4	97526838	4
N/A	Flanges	96983491	1	96983489	1
N/A	Gasket	97692909	1	97692916	1
Kit No. 96967595 2" x 1" CI BLACK for G05 250#		2"		1"	
Pos. No.	Description	Material No.	Qty.	Material No.	Qty.
N/A	Bolts	91120660	8	91130816	4
N/A	Flanges	00ID2743	1	96983493	1
N/A	Gasket	00ID2747	1	97694407	1
Kit No. 97642571 3" x 1.5" CI BLACK for GB, G50 and G20 125#		3"		1.5"	
Pos. No.	Description	Material No.	Qty.	Material No.	Qty.
N/A	Nuts	00ID1510	4	none	0
N/A	Bolts	00ID1921	4	97693886	4
N/A	Flanges	00ID1925	1	91123167	1
N/A	Gasket	560185	1	91123168	1
Kit No. 97658571 3" x 1.5" CI BLACK for GB, G50 and G20 250#		3"		1.5"	
Pos. No.	Description	Material No.	Qty.	Material No.	Qty.
N/A	Bolts	91120662	8	91137423	4
N/A	Flanges	91121943	1	96983494	1
N/A	Gasket	91122339	1	97694408	1
Kit No. 97642574 3" x 2" CI BLACK for GC, G10, G60 and G30 125#		3"		2"	
Pos. No.	Description	Material No.	Qty.	Material No.	Qty.
N/A	Nuts	00ID1510	4	none	0
N/A	Bolts	00ID1921	4	91130816	4
N/A	Flanges	00ID1925	1	96983491	1
N/A	Gasket	560185	1	97692909	1
Kit No. 97658572 3" x 2" CI BLACK for GC, G10, G60 and G30 250#		3"		2"	
Pos. No.	Description	Material No.	Qty.	Material No.	Qty.
N/A	Bolts	91120662	8	91120660	8
N/A	Flanges	91121943	1	00ID2743	1
N/A	Gasket	91122339	1	00ID2747	1
Kit No. 97642568 2" x 2" CI BLACK for G22 125#		2"		2"	
Pos. No.	Description	Material No.	Qty.	Material No.	Qty.
N/A	Bolts	91130816	4	91130816	4
N/A	Flanges	96983491	1	96983491	1
N/A	Gasket	97692909	1	97692909	1
Kit No. 97757976 2" x 2" CI BLACK for G22 250#		2"		2"	
Pos. No.	Description	Material No.	Qty.	Material No.	Qty.
N/A	Bolts	91120660	8	91120660	8
N/A	Flanges	00ID2743	1	00ID2743	1
N/A	Gasket	00ID2747	1	00ID2747	1

ACCESSORIES (Continued)

ANSI COMPANION FLANGES FOR MEDIUM CR-H, CRN-H					
Kit No. 97698645 1.5" x 1" 316SS for GA 150#		1.5"		1"	
Pos. No.	Description	Material No.	Qty.	Material No.	Qty.
N/A	Bolts	97743748	4	97743748	4
N/A	Flanges	96983498	1	96983497	1
N/A	Gasket	97694409	1	97692916	1
Kit No. 97698646 1.5" x 1" 316SS for GA 300#		1.5"		1"	
Pos. No.	Description	Material No.	Qty.	Material No.	Qty.
N/A	Bolts	91143035	8	91143029	4
N/A	Flanges	96983496	1	96983495	1
N/A	Gasket	97694408	1	97694407	1
Kit No. 97698647 2" x 1" 316SS for G05 150#		2"		1"	
Pos. No.	Description	Material No.	Qty.	Material No.	Qty.
N/A	Bolts	91143029	4	97743748	4
N/A	Flanges	96983499	1	96983497	1
N/A	Gasket	97692909	1	97692916	1
Kit No. 97698648 2" x 1" 316SS for G05 300#		2"		1"	
Pos. No.	Description	Material No.	Qty.	Material No.	Qty.
N/A	Bolts	97743741	8	91143029	4
N/A	Flanges	00ID7240	1	96983495	1
N/A	Gasket	00ID2747	1	97694407	1
Kit No. 97698649 3" x 1.5" 316SS for GB, G50 and G20 150#		3"		1.5"	
Pos. No.	Description	Material No.	Qty.	Material No.	Qty.
N/A	Nuts	91143011	4	none	0
N/A	Bolts	91143031	4	97743748	4
N/A	Flanges	91121944	1	96983498	1
N/A	Gasket	560185	1	97694409	1
Kit No. 97698650 3" x 1.5" 316SS for GB, G50 and G20 300#		3"		1.5"	
Pos. No.	Description	Material No.	Qty.	Material No.	Qty.
N/A	Bolts	91143038	8	91143035	4
N/A	Flanges	91121945	1	96983496	1
N/A	Gasket	91122339	1	97694408	1
Kit No. 97698651 3" x 2" 316SS for GC, G10, G60 and G30 150#		3"		2"	
Pos. No.	Description	Material No.	Qty.	Material No.	Qty.
N/A	Nuts	91143011	4	none	0
N/A	Bolts	91143031	4	91143029	4
N/A	Flanges	91121944	1	96983499	1
N/A	Gasket	560185	1	97692909	1
Kit No. 97698652 3" x 2" 316SS for GC, G10, G60 and G30 300#		3"		2"	
Pos. No.	Description	Material No.	Qty.	Material No.	Qty.
N/A	Bolts	91143038	8	97743741	8
N/A	Flanges	91121945	1	00ID7240	1
N/A	Gasket	91122339	1	00ID2747	1
Kit No. 97743809 2" x 2" 316SS for G22 150#		2"		2"	
Pos. No.	Description	Material No.	Qty.	Material No.	Qty.
N/A	Bolts	91143029	4	91143029	4
N/A	Flanges	96983499	1	96983499	1
N/A	Gasket	97692909	1	97692909	1
Kit No. 97743810 2" x 2" 316SS for G22 300#		2"		2"	
Pos. No.	Description	Material No.	Qty.	Material No.	Qty.
N/A	Bolts	97743741	8	97743741	8
N/A	Flanges	00ID7240	1	00ID7240	1
N/A	Gasket	00ID2747	1	00ID2747	1

Spare Part Kits CR15-H

ACCESSORIES (Continued)

Baseplate Kit		Kit No.				
139	56C for GA/B/C	97534517				
	182TC for GA/B/C	97534518				
XLBP1		Kit No.				
	56C for GA/B/C	97534573				
	182TC for GA/B/C		97534574			
Pos. No.	Description	Material No.	Qty. Included in each Kit			
90	Baseplate Cpl. 139, L=991" x W=305" x H=106.4768"	96956336	1	1		
	Baseplate Cpl. XLBP1, L=1500" x W=305" x H=106.4768"	96956376			1	1
N/A	Slider & fastners for 56C (consists of slider & hardware)	96983855	1		1	
N/A	Slider & fastner for 182TC (consists of slider & hardware)	96983858		1		1
N/A	Hardware Kit -96983855/68/78 (cont. pos.56f, g, 90a,d& f)**	97501470	1		1	
N/A	Hardware Kit -96983858 (cont. pos.56f & g, 90a, d & f)**	97501481		1		1
56f	Bolt, Hex Head 1/2 -13 UNC x 1" SAE 5, Zinc plated	N/A	2	2	2	2
56g	Washer, 1/2" SAE, Zinc plated	N/A	2	2	2	2
90a	Bolt, Hex Head 5/16 -18 UNC x .75" SAE 5, Zinc plated	N/A	4		4	
	Bolt, Hex Head 3/8 -16 UNC x .5" SAE 5, Zinc plated	N/A		4		4
90b	Slider, GA/B/C 56C/139BP, L=204" x H=45.5" x W=25.4"	96956339	2		2	
	Slider, GA/B/C 182TC/139 BP, L=230" x H=23" x W=25.4"	96956338		2		2
90d	Bolt, Hex Head 1/4 -20 UNC x 1" SAE 5, Zinc plated	N/A	4		4	
	Bolt, Hex Head 1/4 -20 UNC x 1.75" SAE 5, Zinc plated	N/A		4		4
90f	Washer, 5/16" SAE, Zinc plated	N/A	4		4	
	Washer. 3/8" SAE, Zinc plated	N/A		4		4

* Values in mm, Length (L) is +/- 2mm, Height (H) is +/- 1mm, Width (W). ** Hardware kits 97501470 and 81 are also available for sale.

Baseplate Kit		Kit No.				
148	213TC for GA/B/C	97534520				
	254TC for GA/B/C	97534531				
XLBP2	213TC for GA/B/C	97573875				
	254TC for GA/B/C	97534579				
Pos. No.	Description	Material No.	Qty. Included in each Kit			
90	Baseplate Cpl. 148, L=1219* x W=381* x H=107.9*	96956346	1	1		
	Baseplate Cpl. XLBP2, L=1777.8* x W=381* x H=107.9*	96956377			1	1
N/A	Slider & fastners for 213TC(consists of slider & hardware)	96983859	1		1	
N/A	Slider & fastner 254TC (cont. of 56k , slider & hardware)	96983862		1		1
N/A	Hardware Kit -96983859(consists of pos.56f, g, 90a,d& f)**	97501482	1		1	
N/A	Hardware Kit -96983862 (cont. pos.56f, g & m, 90a, d & f)**	97501483		1		1
56f	Bolt, Hex Head 1/2 -13 UNC x 1.25" SAE 5, Zinc plated	N/A	2		2	
	Bolt, Hex Head 1/2 -13 UNC x 2.25" SAE 5, Zinc plated	N/A		2		2
56g	Washer, 1/2" SAE, Zinc plated	N/A	2		2	2
56k	Volute Spacer, 148 BP 254T, L=200* x H=25.4* x W=78.2	96956349		1		1
56m	Slotted Spring Pin ø3/16" x 1" Zinc Plated	N/A		2		2
90a	Bolt, Hex Head 3/8 -16 UNC x 5/8" SAE 5, Zinc plated	N/A	4		4	
	Bolt, Hex Head 1/2 -13 UNC x 1.5" SAE 5, Zinc plated	N/A		4		4
90b	Slider, GA/B/C 213TC/148BP, L=252* x H=20* x W=25.4*	96956347	2		2	
	Slider, GA/B/C 254TC/148BP, L=299* x H=20.3* x W=38.1*	96956348		2		2
90d	Bolt, Hex Head 1/4 -20 UNC x 1.75" SAE 5, Zinc plated	N/A	4		4	
	Bolt, Hex Head 1/4 -20 UNC x 2.5" SAE 5, Zinc plated	N/A		4		4
90f	Washer, 3/8" SAE, Zinc plated	N/A	4		4	
	Washer, 1/2" SAE, Zinc plated	N/A		4		4

* Values in mm, Length (L) is +/- 2mm, Height (H) is +/- 1mm, Width (W). ** Hardware kits 97501482 and 83 are also available for sale.

Baseplate Kit		Kit No.	
XLBP4		97534594	
284TC for GA/B/C			
Pos. No.	Description	Material No.	Qty. Included in each Kit
90	Baseplate Cpl. XLBP4, L=2406.4* x W=457.2* x H=194*	96957102	1
N/A	Slider & fastners for 284TC (consists of slider & hardware)	96983863	1
N/A	Hardware Kit -96983871 (cont. of pos.56f & g, 90a,d & f)**	97501484	1
56f	Bolt, Hex Head 1/2 -13 UNC x 1.25" SAE 5, Zinc plated	N/A	2
56g	Washer, 1/2" SAE, Zinc plated	N/A	2
90a	Bolt, Hex Head 1/2 -13 UNC x 1.5" SAE 5, Zinc plated	N/A	4
90b	Slider, GA/B/C, 284TC/153BP, L=366* x H=46* x W=25.4*	96956351	2
90d	Bolt, Hex Head 1/4 -20 UNC x 2.25" SAE 5, Zinc plated	N/A	4
90f	Washer, 1/2" SAE, Zinc plated	N/A	4

* Values in mm, Length (L) is +/- 2mm, Height (H) is +/- 1mm, Width (W). ** Hardware kit 97501484 is also available for sale.

ACCESSORIES (Continued)

Baseplate Kit		Kit No.				
245	56C for G05/10/50/60/70/22/33/44	Kit No.	97534535			
	182TC for G05/10/50/60/70/22/33/44	Kit No.	97534536			
XLBP1	56C for G05/10/50/60/70/22/33/44	Kit No.		97534575		
	182TC for G05/10/50/60/70/22/33/44	Kit No.			97534576	
Pos. No.	Description	Material No.	Qty. Included in each Kit			
90	Baseplate Cpl. 245, L=1143" x W=305" x H=106.4768"	96956341	1	1		
	Baseplate Cpl. XLBP1, L=1500" x W=305" x H=106.4768"	96956376			1	1
N/A	Slider & fastners for 56C (consists of slider & hardware)	96983868	1		1	
N/A	Slider & fastner for 182TC (consists of slider & hardware)	96983869		1		1
N/A	Hardware Kit -96983855/68/78 (cont. pos.56f, g, 90a,d & f)**	97501470	1		1	
N/A	Hardware Kit -96983869/79 (cont. pos.56f & g, 90a, d & f)**	97501488		1		1
56f	Bolt, Hex Head 1/2 -13 UNC x 1" SAE 5, Zinc plated	N/A	2	2	2	2
56g	Washer, 1/2" SAE, Zinc plated	N/A	2	2	2	2
90a	Bolt, Hex Head 5/16 -18 UNC x .75" SAE 5, Zinc plated	N/A	4	4	4	4
90b	Slider, G05/22 - 56C/245BP, L=204" x H=125.5" x W=25.4"	96956343	2		2	
	Slider, G05/22 - 182T/245 BP, L=230" x H=100" x W=25.4"	96956342		2		2
90d	Bolt, Hex Head 1/4 -20 UNC x 1" SAE 5, Zinc plated	N/A	4		4	
	Bolt, Hex Head 1/4 -20 UNC x 2.5" SAE 5, Zinc plated	N/A		4		4
90f	Washer, 5/16" SAE, Zinc plated	N/A	4	4		4

* Values in mm, Length (L) is +/- 2mm, Height (H) is +/- 1mm, Width (W). ** Hardware kits 97501470 and 88 are also available for sale.

Baseplate Kit		Kit No.		97534539	
252	213TC for G05/10/50/60/70/22/33/44	Kit No.	97573873		
XLBP2	213TC for G05/10/50/60/70/22/33/44	Kit No.	97573873		
Pos. No.	Description	Material No.	Qty. Included in each Kit		
90	Baseplate Cpl. 252, L=1321" x W=381" x H=107.9"	96956356	1		
	Baseplate Cpl. XLBP2, L=1777.8" x W=381" x H=107.9"	96956377		1	
N/A	Slider & fastners for 213TC(consists of slider & hardware)	96983870	1		1
N/A	Hardware Kit -96983870/80(cont. of pos.56f, g, 90a,d & f)**	97501489	1		1
56f	Bolt, Hex Head 1/2 -13 UNC x 1.25" SAE 5, Zinc plated	N/A	2	2	
56g	Washer, 1/2" SAE, Zinc plated	N/A	2	2	
90a	Bolt, Hex Head 3/8 -16 UNC x 1" SAE 5, Zinc plated	N/A	4	4	
90b	Slider, G05/22, 213TC/252BP,L=252" x H=96.5" x W=25.4"	96956357	2	2	
90d	Bolt, Hex Head 1/4 -20 UNC x 1.75" SAE 5, Zinc plated	N/A	4	4	
90f	Washer. 3/8" SAE, Zinc plated	N/A	4	4	

* Values in mm, Length (L) is +/- 2mm, Height (H) is +/- 1mm, Width (W). ** Hardware kit 97501489 is also available for sale.

Baseplate Kit					
258	254-286TC for G05/10/50/60/70/22/33/44	Kit No.	97534543		
XLBP3	254-286TC for G05/10/50/60/70/22/33/44	Kit No.		97573876	
Pos. No.	Description	Material No.	Qty. Included in each Kit		
90	Baseplate Cpl. 258, L=1473.2" x W=457.2" x H=119.1"	96956360	1		
	Baseplate Cpl. XLBP3, L=2406.4" x W=457.2" x H=119.1"	96956379		1	
N/A	Slider & fastners for 254TC (consists of slider & hardware)	96983871	1	1	
N/A	Hardware Kit -96983871 (cont. of pos.56f & g, 90a,d & f)**	97501493	1	1	
56f	Bolt, Hex Head 1/2 -13 UNC x 1" SAE 5, Zinc plated	N/A	2	2	
56g	Washer, 1/2" SAE, Zinc plated	N/A	2	2	
90a	Bolt, Hex Head 1/2 -13 UNC x 1.25" SAE 5, Zinc plated	N/A	4	4	
90b	Slider, G05/22, 254TC/258BP, L=354" x H=67" x W=25.4"	96956361	2	2	
90d	Bolt, Hex Head 1/4 -20 UNC x 1.75" SAE 5, Zinc plated	N/A	4	4	
90f	Washer, 1/2" SAE, Zinc plated	N/A	4	4	

* Values in mm, Length (L) is +/- 2mm, Height (H) is +/- 1mm, Width (W). ** Hardware kit 97501493 is also available for sale.

Spare Part Kits • Special Tools **CR15-H**

SPECIAL TOOLS

Tools not generally available from normal sources.

Mat. No.	Description and Use	
00SV0040	Shaft Holder for Dismantling/Assembly Used to hold and protect the shaft during dismantling and assembly.	
00SV2107	Tubular Box Spanner for Shaft Seal 41.0 mm Used to install and remove the shaft seal. Fits a 1/2" drive ratchet.	
00SV2101	Ring Insert Tool for Shaft Seal + Square 41 mm x 1/2" drive	
00SV0239	Puller for Neck Ring Used to remove the Neck Ring from Chamber.	
00SV2011	Bit Holder Used with Bits Kit, 1/4"	
00SV2010	Bits Kit NV 5 mm for M6, 1/4" NV 6 mm for M8, 1/4" NV 8 mm for M10, 1/4"	
00SV2012	Hexagon Socket Bit Used for Shaft Seal NV 2.5 mm for M5, 1/4"	
00SV2127	Bearing Removal Punch	

STANDARD TOOLS

In addition to being available from Grundfos, comparable tools can be purchased through normal sources.

Mat. No.	Description and Use	
00SV0083 00SV0055 00SV0054 00SV0122	Wrenches Used to tighten various nuts. NV 10 mm for M6 NV 13 mm for M8 NV 19 mm for M12 NV 24 mm for M16	
00SV0292 00SV0269 00SV0400	Torque Wrench Used to torque various screws. 4-20 Nm, 9 x 12 20-100 Nm, 9 x 12 40-200 Nm, 14x18	
00SV0438	Torque Screwdriver Used to tighten various nuts. 1-6 Nm, 1/4"	
00SV0295 00SV0401	Ratchet Spanner for all Adapters 9 mm x 12 mm, 1/2" 14 mm x 18 mm, 1/2"	
00SV0296 00SV0297 00SV0298	Socket Spanner with Inside Hex NV 5 mm for M6, 1/2" x 1/2" NV 6 mm for M8, 1/2" x 1/2" NV 8 mm for M10, 1/2" x 1/2"	
00SV0310 00SV0294 00SV0271 00SV0524	Ring Spanner NV 10 mm, 9 x 12, for M6 NV 13 mm, 9 x 12, for M8 NV 19 mm, 9 x 12, for M12 NV 24 mm, 14 x 18, for M16	
00SV2013 00SV0267	Socket Spanner NV 13 mm for M8, 1/2" drv. NV 19 mm for M12, 1/2" drv.	

BE > THINK > INNOVATE >

Being responsible is our foundation
Thinking ahead makes it possible
Innovation is the essence



L-CR-SM-052 11/11 US

©2011 Grundfos Pumps Corp.

Subject to alterations.

GRUNDFOS Pumps Corporation
17100 W. 118th Terrace
Olathe, Kansas 66062
Phone: 913.227.3400
Fax: 913.227.3500
www.grundfos.com

GRUNDFOS Canada, Inc.
2941 Brighton Road
Oakville, Ontario L6H 6C9 Canada
Phone: 905.829.9533
Fax: 905.829.9512

Bombas GRUNDFOS de Mexico S.A. de C.V.
Boulevard TLC No. 15
Parque Industrial Stiva Aeropuerto
Apodaca, N.L. Mexico 66600
Phone: 52.81.8144.4000
Fax: 52.81.8144.4010

GRUNDFOS