

IDNRPM21104C - Specifications

Property	Value
Catalog Number	IDNRPM21104C
Enclosure	TENV
Frame	FL2162C
Frame Material	Exposed Laminations
Frequency	60.00 Hz
Motor Letter Type	Three Phase
Output @ Frequency	10.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
Agency Approvals	CCSA US
Auxillary Box	No Auxillary Box
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Current @ Voltage	13.600 A @ 460.0 V
Duty Rating	CONT
Feedback Device	NO FEEDBACK
High Voltage Full Load Amps	13.6 a
Frame Prefix	FL
Heater Indicator	No Heater
Insulation Class	H
IP Rating	NONE
Mounting Arrangement	F3
Overall Length	23.71 IN
Product Family	General Industrial
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Service Factor	1.00
Shaft Diameter	1.375 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Speed	1780 rpm

Motor Standards	NEMA
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat