End Suction Split Coupled Pump

PACO LCS

The LCS single stage, end suction, split coupled pump serves as the industry standard in performance, quality, and durability. The LCS provides hydraulic performance equal to that of a frame mounted, long coupled model, but in a compact design. Advanced features and benefits incorporated as standard, as well as optional features that meet specialized needs, set these high-efficiency, end suction pumps apart as the broadest line offered to the marketplace.

Key Features and Benefits

- · No baseplate grouting required
- Axially split, rigid coupling enhances ease of service with reduced maintenance costs
- No alignment required between the pump and motor eliminates laser alignment costs and reduces installation time
- Optimized, space-saving design has 35% smaller footprint than frame mount design
- Spacer coupling allows rapid mechanical seal access without motor removal for service friendly design
- Vesconite case wear rings extend pump life and increase efficiency
- Double volute design increases efficiency, lowers life cycle costs and prolongs seal and bearing life
- Francis Vane impeller design increases efficiency and reduces NPSH required
- · Reduced installation and wiring cost
- Integrally cast diffuser vane reduces turbulence and need for suction guides
- Trimmed and balanced impellers allow customization, reduce noise and vibration for quiet operation and prolong seal and bearing life
- Large seal chamber allows various seal configurations and customization



APPLICATIONS

- Chilled water
- Condensed water
- Hot water
- District heating/cooling
- HVAC
- Process water
- Light industrial
- Water utility





LCS Technical Data

LCS Information	
Flow, Q	max. 4200 gpm
Head, H	max. 430 ft
Fluid temp.	10° to 275° F
Max. working pressure	max. 175 psi*
HP range	max. 125 Hp
Speed	3600, 1800, and 1200 RPM
Discharge sizes	1 to 8 in.

* 250 psi rating available

