

MYERS® MD SERIES

The Myers MD series 4" stainless steel submersible effluent pumps are capable of drawing down to 4-1/2" (a standard NEMA 4" only draws down to 13-1/2"). Lower amp draw reduces operating costs and extends the life of the float switch contacts. Pumped fluid flows around motor providing cooling and sound dampening. Ideal for on-site filtered and cistern applications.



APPLICATIONS

On-site filtered effluent, cistern

SPECIFICATIONS

Capacities – 2-35 GPM (7.6-132.5 LPM)
Shut-off Head – 75'-225' (22.9-68.6 m)
Max. Spherical Solids – .080" (2.0 mm)
Liquids Handling – Filtered effluent
Max. Liquid Temperature – 86°F (30°C)
Motor/Electrical Data – Dry-wound, double ball bearing, double-seal, thermal overload protected, 115V, 1Ø, 60Hz
Specific Gravity – .9-1.1
Viscosity – 28-35 SSU
Discharge, NPT – 1-1/4"
Housing – Stainless steel and composite
Power Cord – 10' (30 m), 300V, 2-wire with ground, SJTW-A, SJTW

FEATURES

Superior Drawdown

Beats the industry standard for drawdown by 9" (Myers: 4-1/2" vs. NEMA: 13-1/2")

Lower Operating Costs

25% reduced amp draw (9.5A vs. 12.7A for standard NEMA 4")

Cooler and Quieter

Designed to route pumped fluid over motor for cooler operation and reduce noise – eliminates need for expensive "flow-inducer sleeves"

Proven and Patented

Field-proven staging system utilizes patented ceramic wear surface and features industry-exclusive "dry-run" capabilities

Built to Last

Stainless steel and reinforced thermoplastic construction; heavy duty, double-seal, double ball-bearing motor with 7/16" stainless steel shaft

Thermal Protection

Overload protection with automatic reset when motor cools to a safe operating temperature

Protected From Debris

Self-lubricating Nylatron® shaft bearing protects wear surface from sand and abrasives

Serviceable Screen


Field-serviceable composite intake screen – allows up to 0.80" solids

ORDERING INFORMATION

Catalog Number	HP	Volts	Phase/Cycles	Amps	Discharge Size	Switch Type	Cord Length	Approx. Wt. Lbs.
10MD05121	1/2	115	1/60	11	1-1/4"	Manual	10'	19
20MD05121	1/2	115	1/60	9.5	1-1/4"	Manual	10'	19
30MD05121	1/2	115	1/60	9.5	1-1/4"	Manual	10'	19


MYERS® MD SERIES

DIMENSIONS



GPM	Length	Diameter
10	21.6" (549 mm)	3.86" (98 mm)
20	20.8" (529 mm)	3.86" (98 mm)
30	20.6" (523 mm)	3.86" (98 mm)

PUMP PERFORMANCE



USA
 293 WRIGHT STREET, DELAVAN, WI 53115 WWW.FEMYERS.COM
 PH: 888-987-8677 ORDERS FAX: 800-426-9446

CANADA
 490 PINEBUSH ROAD, UNIT 4, CAMBRIDGE, ONTARIO N1T 0A5
 PH: 800-363-7867 ORDERS FAX: 888-606-5484

Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice.