# MYERS® MCSP SERIES

The Myers® MCSP series pedestal sump pumps are industry-proven for reliability and offer an economical choice for new installation or retrofit. Easy to install and an ideal solution for residential basement sump drainage. Available in engineered thermoplastic or cast iron models.

## APPLICATIONS

**Basement sumps** 

## SPECIFICATIONS

Capacities – 52 GPM (197 LPM) Capacities – 50 GPM (189.3 LPM) Shut-off Head – 18' (5.5 m) Operation – On: 12"-13" (305-330 mm) Off: 3"- 4.5" (76-144 mm) Solids Handling – 1/8" (3.18 mm) Liquids Handling – Drain water Liquid Temperature – 77°F (25°C) Motor/Electrical Data – 1/3 HP, 1625 RPM, 115V, 3.5A, 1Ø, 60Hz, permanent split capacitor type

Acceptable pH Range – 6-9

Shaft Seal – None Housing – Thermoplastic or cast iron

Power Cord – 6', 16/3, SJT Discharge, NPT –

MCSP3: 1-1/4" (31.8 mm) NPT F MCSP3I: 1-1/4" (31.8 mm) NPT F or; 1-1/2" (38.1 mm) NPT M **Min. Sump Diameter** – 12" (304.8 mm)



MCSP3 (Thermoplastic) MCSP3I (Cast Iron)

### FEATURES

#### **Powerful Starts**

High-torque, shaded pole motor; no starting switches or relays to wear out

#### **Built to Last**

Permanently lubricated motor and corrosion-resistant shaft for years of reliable service

#### Easy Adjustment

Top-mounted vertical float switch completely accessible for draw-down adjustments

#### **Prevents Overheating**

Heat sensor overload protection with automatic reset when motor cools to a safe operating temperature

## **Resists Clogging**

Top-mounted inlet screen reduces clogging and filters out solids that could damage pump.

#### Fast, Easy Installation

Easy float adjustment and grounded plug on 6-foot cord


## ORDERING INFORMATION

Catalog Number	НР	Volts	Phase/ Cycles	Amps	Discharge Size	Switch Type	Cord Length	Approx. Wt. Lbs.
MCSP3 Thermoplastic	1/3	115	1/60	3.5	1-1/4" NPT (F)	Vertical Automatic	6'	18
MCSP3I Thermoplastic	1/3	115	1/60	3.5	1-1/4" NPT (F) 1-1/2" NPT (M)	Vertical Automatic	6'	24


## MYERS® MCSP SERIES

## DIMENSIONS

MCSP3



PUMP PERFORMANCE





USA 293 WRIGHT STREET, DELAVAN, WI 53115 WWW.FEMEYERS.COM PH: 888-987-8677 ORDERS FAX: 800-426-9446 CANADA 269 TRILLIUM DRIVE, KITCHENER, ONTARIO, CANADA N2G 4W5 PH: 519-606-5484 ORDERS FAX: 800-426-9446

Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice.

© 2012 Pentair Ltd. All Rights Reserved.