

VP3575-14 - Specifications

Property	Value
Armature Voltage	180 V
Base Speed	1750 rpm
Enclosure	TEFC
Frame	D90C
Frame Material	Steel
Output Power	1.500 HP
Haz Area Class and Group	None
Agency Approvals	CE CSA UKCA UR WEEE
Ambient Temperature	40 °C
Armature Current	7.7 a
Armature Inertia	30.342 lb-ft ²
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Drip Cover	No Drip Cover
Duty Rating	CONT
Feedback Device	NO FEEDBACK
Frame Prefix	D
Heater Indicator	No Heater
Insulation Class	F
Lifting Lugs	No Lifting Lugs
Motor Lead Exit	Ko Box
Motor Lead Termination	Flying Leads
Motor Lead Quantity/Wire Size	2 @ 14 AWG, A
Mounting Arrangement	B34
Overall Length	17.63 IN
Product Family	General Purpose
Pulley End Bearing Type	Sealed Bearing
Service Factor	1.00
Shaft Diameter	0.945 IN

Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Motor Standards	IEC
Haz Area Division	Not Applicable