

# SPRINKLER PUMP

## APPLICATIONS

Ideal for both residential and commercial lawn and turf sprinkling systems.

## FEATURES & BENEFITS

- Rugged cast iron casing and pump base
- High efficiency thermoplastic impeller and diffuser
- BR models are configured with a brass impeller which is recommended for more demanding applications such as weir feeders\*
- Easy to prime to 25'; no additional priming required after initial fill



RL-SPRK100



RL-SPRK200

Model	Item No.	UPC	HP	Volts	Amps	Intake	Discharge	Discharge Pressure (PSI) at 5' Lift				Max. Press. (PSI)	Max. Flow (GPM)
								10	20	30	40		
RL-SPRK100	97101001	0 10121 00139 8	1	115/230	14 A @ 115 V / 7 A @ 230 V	2" FNPT	1-1/2" FNPT	63	54	38	11	45	63
RL-SPRK150	97101501	0 10121 00140 4	1-1/2	115/230	18.6 A @ 115 V / 9.3 A @ 230 V	2" FNPT	1-1/2" FNPT	71	60	44	15	44	71
RL-SPRK200	97102001	0 10121 00141 1	2	230	10.9 A @ 230 V	2" FNPT	1-1/2" FNPT	76	75	65	47	49	76
*RL-SPRK-150-BR	97101502	0 10121 00142 8	1-1/2	115/230	18.6 A @ 115 V / 9.3 A @ 230 V	2" FNPT	1-1/2" FNPT	71	60	44	15	41	71
*RL-SPRK-200-BR	97102002	0 10121 00143 5	2	230	10.9 A @ 230 V	2" FNPT	1-1/2" FNPT	77	75	64	48	47	77

## CARTON SPECIFICATIONS

Model	Length	Width	Height	Weight (lbs)	Carton Cubes (cu ft)	Pallet Quantity	Quantity per Layer	Layers per Pallet
RL-SPRK100	11.5"	22"	12.25"	25.02	1.79	18	3	6
RL-SPRK150	11.5"	22"	12.25"	29.32	1.79	18	3	6
RL-SPRK200	11.5"	22"	12.25"	29.15	1.79	18	3	6
*RL-SPRK-150-BR	11.5"	22"	12.25"	30.07	1.79	18	3	6
*RL-SPRK-200-BR	11.5"	22"	12.25"	30.07	1.79	18	3	6

Centrifugal Sprinkler Pumps

