

NEW!

Liberty Pumps®

StormCell®

PC 442-Series



Sump Pump Combo Series

Pre-assembled Primary
Pump and Battery
Backup System

Drop-in-the-pit ready

Features:

- Provides uninterrupted pumping in the event of a power outage or main pump failure
 - Fully assembled
- Primary pumps available in 1/3 and 1/2 hp
- Ready to connect to 1-1/2" discharge pipe
 - Primary pump and backup pump check valves included
- StormCell® 442-Series backup system includes:
 - Audible and visual alarm with super-bright LED alarm
 - Energy efficient 12V DC pump (manufactured in the US by Liberty)
 - Professional -grade 10 amp charger/controller
 - Battery box (fits Group 27 or 31 batteries)
 - User interface with LCD readout
 - Compact float system
 - Silence and Test buttons
 - Auxiliary contacts
- Suitable with AGM, Wet Cell or Gel type batteries (not included) Liberty StormCell® batteries recommended for optimum performance



NightEye®
Wireless Enabled
Model Available

PC 442-Series


Sump Pump Combo Series



Models	Description	Primary Pump	NightEye Wireless Enabled	System Weight
PC237-442-10A	Model 237 and 442	1/3 hp, 115 V, 5.2 amp	No	30 lbs.
PC257-442-10A	Model 257 and 442	1/3 hp, 115 V, 5.2 amp	No	42 lbs.
PC457-442-10A	Model 457 and 442	1/2 hp, 115 V, 7.3 amp	No	32 lbs.
PCS37-442-10A	Model S37 and 442	1/3 hp, 115 V, 6.2 amp	No	33 lbs.
PC237-442-10A-EYE	Model 237 and 442	1/3 hp, 115 V, 5.2 amp	Yes	30 lbs.
PC257-442-10A-EYE	Model 257 and 442	1/3 hp, 115 V, 5.2 amp	Yes	42 lbs.
PC457-442-10A-EYE	Model 457 and 442	1/2 hp, 115 V, 7.3 amp	Yes	32 lbs.
PCS37-442-10A-EYE	Model S37 and 442	1/3 hp, 115 V, 6.2amp	Yes	33 lbs.

Minimum pit size for all above systems 18" diameter x 18" deep. For complete primary pump specifications see appropriate 230-Series, 250-Series, 450-Series or S30-Series literature. For complete back-up pump specifications see StormCell® 442-Series literature.

Primary Pump Performance




Included in complete system

- Primary Pump, 115 V
- 442-10A backup pump system
- 1-1/2" PVC piping with rubber coupler between primary pump and back-up pump (rubber coupler provides easy removal and serviceability of back-up pump)
- Check valve included on primary pump and back-up pump
- Completely assembled
- Maximum fluid temperature 140° F
- Battery not included. 12 volt deep cycle battery Group 27 or 31 recommended

For optimum performance, Liberty StormCell® batteries recommended

Back-Up Pump Performance

Model 442-10A



Primary Pump Options



Liberty Pumps ■ 7000 Apple Tree Avenue ■ Bergen, New York 14416 ■ Phone 800-543-2550 ■ Fax (585) 494-1839

libertypumps.com