SUBMERSIBLE MOTOR INSTALLATION RECORD Form 2207 - Page 1

		V		•	1	T	Ļ	î	î	b	e	í
--	--	---	--	---	---	---	---	---	---	---	---	---

	KEY DEALER #	
DISTRIBUTOR	INSTALLER	END USER
Name:	Name:	Name:
City:	City:	City:
State: Zip:	State: Zip:	State: Zip:
Well ID or GPS:		Water Temperature: °F °C
Application/Water Use (e.g. potable water	, irrigation, municipal, fountain,	etc.):
Date Installed (mm/yy):	Date Failed (mm/yy):	Motor Position Shaft-Up: Yes No
Operating Cycle: ON Time Per Start	Hrs Mins. Time OFF	Between Stop & Restart Hrs. Mins.
MOTOR		
Model: Seria	ıl Number:	Date Code (if updated):
MOTOR OVERLOAD		
System Typical Operating Current:	Amps @	Volts
	WELL DAT	(All measurements from well head down.)
Manufacturer:		Casing Diameter in
Model:		Drop Pipe Diameter in
Stages:		Number of Sticks of Drop Pipe
Design Rating: gpm @	_ft TDH	Static Water Level ft
Horsepower Required by Pump End:	▼	Drawdown (pumping) Water Level ft
Actual Pump Delivery: gpm @ _	psi	Spring Assist Check Valves:
What Controls When System Runs & Stop	os:	(Measured from Well Head Down) #1 #2 #3 #4 ft
(e.g. pressure level flow manual on/off t		Solid Drilled Poppet Break-Off Plug
time clock etc.)		Pump Inlet Setting ft
		Flow Sleeve 🗌 No 🗌 Yes, Dia in
		Case Ends ft
		/ 🗌 Well Screen 🗌 Perforated Casing
YOUKTWAIME/ DATE		#1 fromtoft & #2 fromtoft
/	[] 🗸	Well Depth ft

Form No. 2207 v6 05/11 © 2009 Franklin Electric Co., Inc.

This material may be reproduced in its entirety for personal and educational purposes, including reproduction in technical specifications and manuals, without prior permission, provided that the above copyright notice is included in all copies or substantial portions of the material. All other rights reserved.



SUBMERSIBLE MOTOR INSTALLATION RECORD Form 2207 - Page 2

řA

	hree Tra	nsformers Su	pply Motor Oply:		
ransformer #1: kVA Tra	nsformer #2:		VA Transformer #3	3: kVA	
OWER CABLES & GROUND W	/IRE				
Service Entrance to Pump Control	Panel:				
Length: ft. & Gauge:	A\	NG/MCM			
Material: Copper Aluminum	Cons	truction: 🗌 J	acketed 🗌 Individua	al Conductors 🗌 Web 🔲	Twiste
Temperature Rating of Cable: 60]90C ∐ 125	C or Insulation Type	e: (e.g.	IHHN
Pump Control Panel to Motor:	۸۱				
Material: Copper Aluminum	Av		acketed 🗌 Individua	al Conductors 🗌 Web 🔲	Twiste
Temperature Rating of Cable: 600	C 75C]90C [] 12t	C or Insulation Type	e: (e.g.	THHN
Ground Wire Size: From Control Par	nel to Motor: _	A	WG/MCM		
Control Grounded to (mark all that ap	oply):				
Well Head Metal Casing	Motor Dri	ven Rod 🗌 I	Power Supply		
ICOMING VOLTAGE		▐■■┥ ┡	RUNNING AMPS	& CURRENT BALAN	9 =
o Load L1-L2 L2-L3	L1-L3	F	Full Load L1	L2 L3	
III Load L1-L2 L2-L3	L1-L3	G	% Unbalance:	-	
ONTROL PANEL					
Pump Panel Manufacturer/Fabricat	tor:				
Short Circuit Protection - Fuses or	Circuit Brea	ker			
Option #1 - Fuse					
Manufacturer:	Model:		Rating:	Amps	
Type: 🗌 Time-Delay 🗌 Standard	i				
Option #2 - Circuit Breaker					
Manufacturer:	Model:		Rating:	Amps Setting:	
Starter - Full Voltage, Reduced Volt	age, Soft-Sta	rter or VFD (Variable Frequency	Drive)	
Option #1 - Full Voltage					
Manufacturer:	Model:		Size:	Contacts: NEMA	
Option #2 - Reduced Voltage					
Manufacturer:	Model:		Ramp Time to	o Full Voltage:	se
Option #3 - Soft-Starter or VFD					
Monufacturar	Model:		Max. Continu	ous Amp Output Rating:	
	3PM:		Max. Setting:	Hz & GPM:	
Min. Setting: Hz & (Ston Mode	Power Off Coast	30-0 Hz Ramp	sec
Manufacturer Min. Setting: Hz & 0 Start Ramp Time to 30 Hz:	sec.	otop mode.			
Manufacturer Min. Setting: Hz & (Start Ramp Time to 30 Hz: Special Output Filter Purchased: [sec.] Yes 🛄 No	otop mode.			
Manufacturer: Hz & 0 Min. Setting: Hz & 0 Start Ramp Time to 30 Hz: Special Output Filter Purchased: [Output Filter Manufacturer:	sec.] Yes [_] No	Mode	l:	% Reactance:	